
TOSHIBA

Transistor Inverter



Flexible for you

I need the most suitable inverter for my application, which has low noise, low harmonics, minimal parameter setting, high torque and control.

We meet all your requirements with VF-AS1.

It has outstanding Performance, including high torque, fast response, high accuracy and excellent environmental compatibility with easy operation.

The VF-AS1 is an advanced inverter evolved to satisfy all your needs








- Built-in thermal protection function which complies with NEC® 2005
- Comply with SEMI F47(Semiconductor Equipment and Materials International)







For your Commercial facilities, offices and factories

- Feature: Reduce high-frequency noise*1, Reduce harmonics*1
- Applications: Washing machines, Treadmill, Showcase refrigerators, Medical equipment, stage equipment

For machinery that requires simple function

- Feature: EASY key, 8 basic parameters
- Applications: Drilling machines, Handling machines, Conveyors, Semiconductor production Equipment, Cutting machines, Woodworking machinery

For machinery that requires high torque and a large capacity

- Feature: Starting torque of 0.3Hz-200%*2, Up to 500kw for a 400V class
 - Applications: Cranes, Mining machinery, refrigerator, Presses, Compressers,
 Crushing machine

For system devices that requires flexibility

- Feature: My function, High-precision and high-speed torque control with or without sensors
- Applications: Process lines, Printing machines, Coilers/uncoilers

Renewal: "Power Removal" safety function*3

Built-in Power Removal safety function which complies with EN954-1 category 3 and IEC/EN61508-1 SIL2.

It saves the installation of a line side or motor side contactor.



- *1 Depends on the voltage and capacity range
- *2 When a TOSHIBA standard 3-phase, 0.4 to 3.7kw 4-pole motor are driven
- *3 The units with the type-WN1 or WP1 have Power Removal safty function.

Voltage Class											A	Applicat	ble Mot	or Out	out (kV	V)										
(input/rated output)	0.4	0.75	1.5	2.2	3.7	5.5	7.5	11	15	18.5	22	30	37	45	55	75	90	110	132	160	200	220	280	355	400	500
3ø200V/3ø200V																										
3ø400V/3ø400V																										
	\ \																									

 $\ \, \text{Up to 5.5kw, 3-phase 200V class can be applied to 1-phase input power supply by using 1 size-up rating } \\$

Contents	
For your commercial facilities, offices and factoriesP3	External dimensions P13
For machinery that requires simple function P4	Standard connection diagrams P17
For machinery that requires high torque and a large capacityP5	Terminal functions P18
For system devices that requires flexibility P6	For inverter users P19
For machinery that requires expansion P7	Peripheral devices P22
Function Description P9	Built-in options P23
Standard specifications P10	External options P24

For your commercial facilities, offices and factories



This makes the inverter ideal for your electronic applications such as washing machines treadmill, showcase refrigerators for stores, medical equipment, and stage equipment where attention must be paid to peripheral devices.

*1:Photos of machinery are for illustrative purposes only.


For machinery that requires simple function



This makes the inverter ideal for drilling machines, handling machines, conveyors, semiconductor production equipment, cutting machines, and woodworking machinery that require simple function.

*1:Photos of machinery are for illustrative purposes only.

Harmonics Reduction, Power Factor Improvement




 A compact, space-saving new type of DC reactor is built into 200 V class 11 to 45 kW and 400 V 18.5 to 75 kW models

In addition to reducing harmonics, this reactor limits the input current to 110% of the rated output current, and it has been designed to be compatible with power supply systems containing transformers, molded-case circuit breakers, and power lines.

Adding on the optional DC reactor enables compliance with IEC harmonics standards.

High-frequency Noise Reduction



• High-frequency noise is drastically reduced on models with built-in noise filters. Built-in noise filters are ideal for sites from commercial facilities and offices through to factories where attention must be paid to peripheral devices.

Compared with filter not integrated models, space and wiring savings have been achieved by incorporating the filter in the panel. Also, models with built-in EMC noise filter comply with the European EMC Directive as individual inverter units.

European EMC Directive : IEC/EN61800-3, 1st Environment, C2 $\begin{pmatrix} 200V-0.4 \text{ to } 1.5 \text{kW} \\ \text{or} \end{pmatrix}$ or $\begin{pmatrix} 200V-0.4 \text{ to } 1.5 \text{kW} \\ 400V-0.75 \text{ to } 3.7 \text{kW} \end{pmatrix}$

IEC/EN61800-3, 2nd Environment, C3



200V class models, 0.4 to 7.5kW: EMI noise filter (complies with the European EMC Directive) built-in standard
200V class models, 11 to 45kW: Basic noise filter (not complies with the European EMC Directive) built-in standard
400V class models, 0.75 to 75kW: EMI noise filter (complies with the European EMC Directive) built-in standard
400V class models, 90 to 500kW: EMI noise filter (complies with the European EMC Directive) built-in standard

Simple Setup by EASY Key



Quick mode (EASY

Title	Function
AUY	Parameter setting macro function
PE	V/f control mode selection
FH	Maximum frequency
REE	Acceleration time 1
d E C	Deceleration time 1
EHr	Motor overload protection level 1
FΠ	FM terminal meter adjustment
PSEL	Parameter display selection

- In the Quick mode, pressing the EASY key on the panel allows you to operate the inverter by eight basic parameters.
- When setting each of the functions, press the EASY key to move to the standard mode by one-touch operation. In this mode, you can access all parameters.
- You can customize the Quick mode display, maximum of 32 target parameters are displayed to suit your specific setup requirements.
- You can also use the EASY key as a panel/remote key to switch between panel and remote operation, and as a shortcut key to directly access any specific setup or display screen.

Easy Installation, Easy commissioning, and Easy maintenance



Side-by-side installation



Removable control terminal board



Side-by-side installation

 Side-by-side installation of inverters is possible up to the inverter's total capacity. This allows effective utilization of space inside control panels. Heat sink can be installed outside of the panel as an option.

Removable control terminal board

• A removable terminal board is used. This allows you to use the control wiring when replacing the inverter, which also makes maintenance easier.

ON/OFF control of cooling fan

 Temperature-based ON/OFF control reduces noise while the inverter is being stopped, saves energy and extends the cooling fan's life.

Monitoring of serviceable parts/alarm output

 The expected replacement cycle of main circuit capacitors, capacitors on control board, and cooling fan is monitored, and an alarm is output when the cycle is reached.


For machinery that reguires high torque and a large capacity



This makes it ideals for cranes, mining machinery, refrigerator, presses, compressers, crushing machine and other machinery that require a high torque and large capacity.

*1: Photos of machinery are for illustrative purposes only.

Excellent Motor Control Performance



Fast recovery against

- Motor constants required for vector control can be easily set by auto-tuning to enable 1:120 speed control. Moreover, the VF-AS1 also features a robust structure that is unlikely to be influenced by motor temperature.
- On inverters provided with a sensor, high-torque operation of 200%*2 from zero velocity is possible, achieving a speed control range of 1:1000.
- High-speed response frequencies of 40 Hz without sensor and 50 Hz with sensor are achieved respectively, to maintain fixed speed in response to sudden changes in load.
- Modifying software enables high-frequency output up to 1000 Hz, which is ideal for spindle rotation of woodworking and metalworking machinery.
- *2: When a TOSHIBA standard 3-phase, 0.4 to 3.7 kW 4-pole motor are driven.

Dedicated Functions Ideal for Lifting Applications



Fast response


Brake sequence/light-load, high-speed functions

• The inverter has two built-in functions, the brake sequence function and light-load, high-speed function, as standard. The brake sequence function measures the timing with braking by an external motor to achieve smooth operation at start and stop of braking operation. The light-load, high-speed function automatically increases the speed when operating light loads according to the lifting load to improve conveyance efficiency. A learning function for setting and storing to memory required parameters while performing actual operations is also provided to facilitate adjustments.

Built-in transistor for dynamic braking

 The VF-AS1 has a built-in transistor for dynamic braking up to 160 kW, which makes it ideal for lifting applications.

For system devices that requires flexibility



This makes the inverter ideal for process lines, printing machines, coilers/uncoilers.

*1:Photos of machinery are for illustrative purposes only.

Customizing by "My Function"

My function

Number of program steps: 28
Internal relays: 8
Internal counters: 2

Logic commands : ST, STN, AND,

ANDN, OR, ORN, SET. RSET.

HOLD

ON/OFF DELAY TIMER

Data commands : EQ, NE, GT, GE,

LT, LE, ASUB

- With "My function", you can create programs containing up to 28 steps. This achieves logic operations and internal data operations. Parameters can also be set according to analog input and minimum-peak hold of analog outputs. For example:
- (Ex.1) Inverter is automatically switched to commercial operation without the external sequence when the inverter is tripped.
- (Ex.2) A signal is output when torque reaches 120% and frequency is 5 Hz.
- (Ex.3) "Forward rotation operation," "preset-speed operation frequency 3" and "No.2 acceleration/deceleration" are simultaneously turned ON by input on a single terminal.
- (Ex.4) The acceleration/deceleration time is changed dynamically by a voltage within the range 0 to 10 V.

Communications and Network

Programmable controller

RS-485 communications

 RS-485 communications is equipped as standard, and Modbus-RTU protocol is supported in addition to TOSHIBA protocol.

Network options

 Use of communication options enables support of DeviceNet*2, PROFIBUS and CC-Link*3 and other main fieldbuses.

Data tracing

- The PCM001Z communications software allows you to edit, monitor, and trace parameter data on a PC, enabling easier data management from inverter startup through to maintenance.
- *2: DeviceNet is a registered trademark of ODVA (Open DeviceNet Vendor Association).
- *3: CC-Link is a registered trademark of Mitsubishi Electric Corporation.

5

For machinery that requires expansion

9

Outstanding Lineup of Options

LCD Extension Panel Option



This panel is an 23-character x 8-line display, and can be used for simple setup and monitoring by selection of parameters using the jog dial. The display language can be switched between English and Japanese. (German, Italian, Spanish, and Chinese will be available soon.) Type: RKP004Z

P	arameter Setup Mode	
	Quick mode	
AU4	: Auto fnct set	
Pt	: Cntl mode slct	
FH	: Max frequency	
ACC	: Accel time 1	
DEC	: Decel time 1	
To	D D D	₹

Status Monitor Mo	de
Real-time informat	tion 🔼
Rotative direction	Fwd
Frequency reference	10.4Hz
Output current	2%
Input voltage	99%
Output voltage	20%
Top 🖸 🚨	Prm 🗹

^{*}The photograph shows a screen


LED Extension Panel Option



Our customers require a "display that is easily visible from a long way away." In response to this need, we developed this panel using 20 mm LEDs, the largest in its class in the market, to ensure outstanding visibility.

It has also been designed to be fitted into panels for use as an extension panel or display.

In addition, it can be used as a parameter copy and is capable of storing parameters for up to three models.



Type: RKP002Z

Expanded Terminal Block Option Fieldbus Option





This I/O terminal block can be added on to enhance your system for extra compatibility with a wide range of systems:

- Contact inputs (4) Contact outputs (2) Analog inputs (2)

- Analog outputs (2) PTC input (1) Relay output (1 circuit)
- Pulse train input (1)
- Type: ETB003Z, ETB004Z

Main fieldbuses are supported to enable connection to a host controller to achieve savings in space and centralized control of systems.

- DeviceNet*1
- PROFIBUS
- CC-Link*2

- Type: DEV002Z
- Type: PDP002Z
- Type: CCL001Z
- *1 DeviceNet is a registered trademark of ODVA (Open DeviceNet Vendor Association).
- *2 CC-Link is a registered trademark of Mitsubishi Electric Corporation

Encoder Feedback Option



Three encoder feedback options are provided to match output for support of vector control with a sensor.

- Line driver output (RS-422)
- ,Type: VEC007Z
- Open collector/complimentary output (12 V) ,Type: VEC004Z
- Open collector/complimentary output (15 V) ,Type: VEC005Z

Wide Range of Applications

Safety Environmental Compatibility

Ambient temperature 60°C

The VF-AS1 can be used at a rating up to an ambient temperature of 50°C and in environments up to 60°C at a derating current.

Eco Design

88% of materials used on the VF-AS1 are recyclable, which design more than meets of the European WEEE (Waste Electrical and Electronic Equipment) Directive of 70%.

Various Drive Performance

Permanent Magnet Motor (PM) Drive

The PM is driven efficiently by a TOSHIBA oriented control argorithm to achieve savings in energy and space.

High-frequency 1000 Hz Output

Software modification increases output up to a high frequency of 1000 Hz, making it ideal for woodworking and metalworking machinery.

New DC Braking

A newly developed DC braking function allows the stop time to a quarter of that on conventional models.

A Further Enhanced of Functions

Multi-PID Control

As well as process-type PID control (e.g. temperature, pressure, flow rate), the VF-AS1 incorporates speed-type PID control that is compatible with speed feedback, for example, in follow-up operation or winding, for line compatibility with line control.

- Traverse
- Power interruption synchronized control
- Drooping
- Speed gain switching
- Zero speed lock
- Dwell

Two extra controls are achieved, traverse control during rewinding that is mandatory on fabric machinery, and power interruption synchronized control for preventing thread breakage when a power interruption occurs.

Drooping distributes the load of 2-shaft drive on conveyance machinery, for example. Speed gain switching enables adaptation to changes in inertia during operation. Zero speed is hold when the inverter is stopped. And dwell controls acceleration/deceleration, for example, when conveying heavy loads.

Basic functions


Each "setup item" that determines the control characteristics of the inverter is called a "parameter." For example, to change the acceleration time, you choose the acceleration time parameter (titled " # [[").

Quick mode (EASY)

To enter the Quick mode, press the EASY key on the panel. In this mode, you can set eight of the basic parameters.

Standard mode

In this mode, you can set all parameters. For details of parameters, refer to the Instruction Manual.



Basic parameters

Title	Function	Adjustment	Range			Default
F [Frequency of operation panel	LL-UL Hz	nange			Delault 0
, ,	Prequency of operation panel	LE ULTIZ				- U
Title	Function	Adjustment	Range			Default
ЯИН	History function					-
AUI	Automatic acceleration/deceleration	0:Deselect 1:Auto	matic setting 2:Automatic setting (du	ring acceleration only)		0
RU2	Automatic torque boost	0:Deselect 1:Auto	matic torque boost + auto-tuning 1 2	Sensorless vector control 1+ auto-tuni	ng 1	0
ЯЦЧ	Automatic function setting	0:Disabled 1:Freq	uency setting by means of voltage 2:	Frequency setting by means of current		0
		3:Voltage/current	switching from external terminal 4:Fr	equency setting on operation panel and	operation by means of terminals	
			ng and operation on operation panel			
EUOA	Command mode selection			led (including LED/LCD option input)		0
	-		. ,	ternal RS485 (4-wire) communication in	put 4:Communication option input	_
FNOd	Frequency setting mode selection 1		rrent input) 2:RR/S4 (potentiometer/v			2
		1 '	I input enabled (including LED/LCD of		tion input 7:Communication entire input	
				2 (voltage/current input) 10:UP/DOWN 1	tion input 7:Communication option input	
		1	llse input 13:Binary/BCD input	(voltage/current input) 10.017DOWN 1	requericy 11.111 pulse input	
PE	V/f control mode selection			curve 2:Automatic torque boost 3:Senso	orless vector control 1 (speed)	0
, -			•	oint setting 6:PM control 7:PG feedback	11 /	
			or control 2 (speed/torque)		(.,,	
uЬ	Manual torque boost 1	0.0~30.0%				Depends on the capacity
υL	Base frequency 1	25.0~500.0Hz				WN1:60, WP1:50.0
uLu	Base frequency voltage 1		80V 400V class:50~660V			Depends on the capacity
FH	Maximum frequency	30.0~500.0Hz				80.0
UL	Upper limit frequency	0.0~ F H Hz				WN1:60.0, WP1:50.0
LL	Lower limit frequency	0.0~ <i>U L</i> Hz				0.0
REE	Acceleration time 1	0.1~6000 sec.				Depends on the capacity
<u> </u>	Deceleration time 1	0.1~6000 sec.				Depends on the capacity
Rufz	RR/S4 input point 2 frequency	0.0~ F H Hz				WN1:60.0, WP1:50.0 WN1:60.0, WP1:50.0
8 1F 2 5 - 1	VI/II input point 2 frequency Preset speed operation frequency 1	0.0~ F H Hz L L~ U L Hz				0.0
5 r 2	Preset speed operation frequency 2	LL~ULHz				0.0
5-3	Preset speed operation frequency 3	L L~ UL Hz				0.0
5-4	Preset speed operation frequency 4	L L~ UL Hz				0.0
5 - 5	Preset speed operation frequency 5	L L ~ U L Hz				0.0
5-6	Preset speed operation frequency 6	L L ~ U L Hz				0.0
5-7	Preset speed operation frequency 7	L L~UL Hz				0.0
Fr	Forward run/reverse run selection			everse switchable on operation panel)		0
	(operation panel operation)	-	orward/reverse switchable on operation	n panel)		
EHr	Motor overload protection level 1	10~100%				100
OLN	Motor overload protection characteristic selection	Setting	Motor type	Overload protection (protect)	OL stall	0
		0	Standard Motor	(protect)	O (stall)	
		2 3	Standard Wotor	× (not protect) × (not protect)		-
		4		O (protect) O (protect)	× (not stall)	
		6	VF Motor	★ (not protect)	(stall) (not stall) (stall)	
dSPU	Current/voltage unit selection	0:%, 1:A (ampere)/V (volt)	× (not protect)	(Stail)	0
FNSL	FM terminal meter selection			e, 2:Output current, 3:Input voltage, 4:0	Output voltage, etc.)	0
FN	FM terminal meter adjustment	-		•		-
ANSL	AM terminal meter selection	0~64 (0:Output fro	equency, 1:Frequency command valu	e, 2:Output current, 3:Input voltage, 4:0	Output voltage, etc.)	2
AU	AM terminal meter adjustment	-				-
[F	PWM carrier frequency		e capacity model 2.5~8.0kHz)			Depends on the capacity
U u 5	Auto-restart control selection		uto-restart 2:ST ON/OFF switching 3			0
UUE	Regenerative power ride-through control		er ride-through 2:Deceleration stop d			0
			eceleration/acceleration (synchronize			
0.	Dynamic braking selection			d acceleration/deceleration signal+pow t) 2:Select (braking resistance overload		0
Pbr	Dynamic braking selection Dynamic braking resistance	0:Deselect 1:Sele	or foregring resistance overload detec	a, z. select (braking resistance overload	THOI GELECT)	Depends on the capacity
P6[P	Allowable continuous braking resistance	0.01~600.0kW				Depends on the capacity
EYP	Factory default setting		It setting 2:60 Hz default setting 3:Fa	ctory default setting 4:Trip cleared 5:Cu	mulative operation time cleared	0
	,		-	recorded 8:Item 7 above reset 9:Cum		_
				0.0 sec. 11:Acceleration/deceleration t		
PSEL	Parameter display selection	0:Standard setting	g mode at time of activation of motor	1:Quick mode at time of activation of m	otor 2:Quick mode only	0
FI~ F9	Extended parameters	Set parameters in	more detail.			-
G r .U	Automatic edit function	-				-

Extended parameters

About 500 extended parameters are available. For details on extended parameters, please visit our web site (http://www.inverter.co.jp/).

Standard specifications

■ Standard specifications (200 V class - 0.4 to 45 kW, 400 V class -0.75 to 75 kW model)

200 V class

	Item							Specifi	cation						
App	olicable Motor (kW)	0.4	0.75	1.5	2.2	3.7/4.0	5.5	7.5	11	15	18.5	22	30	37	45
	Туре							VFA	S1-						
	Form	2004PL	2007PL	2015PL	2022PL	2037PL	2055PL	2075PL	2110PM	2150PM	2185PM	2220PM	2300PM	2370PM	2450PM
g	Output Capacity (kVA) Note 1)	1.1	1.8	3.0	4.2	6.7	10	13	21	25	29	34	46	55	67
Rating	Output Current (A)	3.0	4.8	8.0	11	17.5	27.5	33	54	66	75	88	120	144	176
۳	Note 2)	(3.0)	(4.5)	(8.0)	(10.5)	(16.6)	(25.0)	(33)	(49)	(64)	(66)	(75)	(88)	(120)	(140)
	Output Voltage		3-phase, 200 to 240 V (The maximum output voltage is the same as the input voltage.)												
	Overload Current Rating		150%–1 minute												
၁ ည	Dynamic		Built-in												
Electric	Braking Circuit		Built-In												
֓֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞֞	Dynamic Breaking Resistor	Compatible with external options													
Power Supply	Voltage/frequency	3-phase, 200 to 240 V – 50/60 Hz													
Sug	Allowable Fluctuation	Voltage +10% - 15% Note 3) Frequency ±5%													
Pro	tective method		IP20 enclosed type (JEM1030) IP00 open type (JEM1030) Note 4)												
Cod	oling method							Forced a	ir cooling)					
Cod	oling fan noise (dBA)	43	43	43	55	55	56	58	60	60	60	60	64	64	64
Col	or							RAL	7016						
Buil	lt-in Filter			EMI no	ise filter	Note 5)					Basic ı	noise filte	er Note 6)		
DC	Reactor			External option Built-in											

400 V class

	Item							Sn	ecificati	on						
Apı	plicable Motor (kW)	0.75	1.5	2.2	3.7/4.0	5.5	7.5	11	15	18.5	22	30	37	45	55	75
, (P)	Type	00	VFAS1-													
	Form	4007PL	4015PL	4022PL	4037PL	4055PL	4075PL	4110PL	4150PL	4185PL	4220PL	4300PL	4370PL	4450PL	4550PL	4750PL
_	Output Capacity (kVA) Note 1)		3.1	4.4	8.0	11	13	21	25	31	37	50	60	72	88	122
Rating	Output Current (A)	2.3	4.1	5.8	10.5	14.3	17.6	27.7	33	41	48	66	79	94	116	160
8	Note 2)	(2.3)	(4.0)	(4.6)	(8.6)	(13)	(17)	(25)	(32)	(37)	(38)	(53)	(60)	(75)	(93)	(120)
	Output Voltage	, ,	3-phase, 380 to 480 V (The maximum output voltage is the same as the input voltage.)													
	Output Voltage Overload Current Rating		150%—1 minute													
. <u>o</u> g	Dynamic															
Electric Braking	Braking Circuit		Built-in													
回面	Dynamic Breaking Resistor	Compatible with external options														
ver	Voltage/frequency	3-phase, 380 to 480 V – 50/60 Hz														
Power Supply	Allowable Fluctuation	Voltage +10% - 15% Note 3) Frequency ±5%														
Pro	tective method		IP20 enclosed type (JEM1030) IP00 open type (JEM1030) Note 4)													
Co	oling method							Force	ed air co	oling						
Co	oling fan noise (dBA)	43	43	43	55	56	56	58	60	60	60	64	64	64	64	64
Co	lor							ı	RAL7016	3						
Bui	ilt-in Filter							EMI no	oise filter	Note 5)						
DC	Reactor				Externa	l option							Built-in			

Note 1) Capacity is calculated at 220V for the 200V models and at 440V for the 400V models.

Note 2) Rated output current when the PWM carrier frequency (parameter $\not\subset F$) is 4kHz or less.

The values between parentheses refer to rated output currents when set to 12kHz.

Note 3) ±10% when the inverter is used continuously (load of 100%)

Note 4) Inverters, 18.5kW or greater, do not have wiring port covers. They have large openings, but there is no space to bend the external cables inside the unit. If they are fitted external to the cabinet, please use an optional wiring port cover.

Note 5) Complies with the Europian EMC Directive

IEC/EN61800-3, 1st environment, category C2 or IEC/EN61800-3, 2nd environment, category C3

Note 6) Not complies with the European EMC Directive

Core and capacities with external filter (optional) : Complies with the Europien EMC Directive

Standard specifications

■ Standard specifications (200 V class -55 to 75 kW, 400 V class -90 to 500 kW model)

		200 V class							
	Item	Specifi	cation						
Ар	plicable Motor (kW)	55	75						
	Туре	VFA:	S1-						
	Form	2550P	2750P						
Rating	Output Capacity (kVA) Note 1)	84	109						
Rat	Output Current (A) Note 2)	221	285						
	Output Voltage	3-phase, 200 to 240 V (The maximum output	ut voltage is the same as the input voltage.)						
	Overload Current Rating	150%–1	minute						
ig di	Dynamic	Buil	t-in						
Electric Braking	Braking Circuit	Buil	C 111						
шб	Dynamic Breaking Resistor	Compatible with	external options						
<u></u>	Voltage/frequency	3-phase, 200 to 240 V – 50/60 Hz	3-phase, 200 to 220 V - 50 Hz						
Power	·	5-priase, 200 to 240 V = 50/60 Hz	3-phase, 200 to 240 V - 60 Hz						
пS	Allowable Fluctuation	Voltage +10% - 15% N	Note 3) Frequency ±5%						
Pro	otective method	IP00 open type (JEM1030) Note 4)						
Co	oling method	Forced ai	r cooling						
Co	oling fan noise (dBA)	61	72						
Co	lor	RAL7016							
Bu	ilt-in Filter	External filter	External filter (optional)						

400 V class

Attached DC reactor Note 5)

	Item					Specifi	cation						
Ap	plicable Motor (kW)	90	110	132	160	200	220	280	355	400	500		
	Type		I.	<u>I</u>	<u>I</u>	VFA	S1–						
	Form	4900PC	4110KPC	4132KPC	4160KPC	4200KPC	4220KPC	4280KPC	4355KPC	4400KPC	4500KPC		
Rating	Output Capacity (kVA) Note 1)	136	164	197	239	295	325	419	511	578	717		
Rat	Output Current (A) Note 2)	179	215	259	314	387	427	550	671	759	941		
	Output Voltage		3-phase, 380 to 480 V (The maximum output voltage is the same as the input voltage.)										
	Overload Current Rating		150%–1 minute										
.2 E	Dynamic		Built-in Compatible with external options										
Electric	Braking Circuit		Compatible with external options										
шб	Dynamic Breaking Resistor		Compatible with external options										
<u></u> = 0	Voltage/frequency	Note 6)	3-phase, 380 to 440 V – 50 Hz										
Power	·	140(6-0)	3-phase, 380 to 480 V – 60 Hz										
шS	Allowable Fluctuation	Voltage +10% - 15% Note 3) Frequency ±5%											
Pro	otective method				IP00	open type (JEM1030) N	ote 4)					
Co	oling method					Forced a	ir cooling						
Co	oling fan noise (dBA)	61	72	73	73	76	76	76	76	76	78		
Co	lor					RAL	7016						
Bu	ilt-in Filter	EMI noise filter Note 7)											
DC	Reactor				Д	ttached DC	reactor Note	5)					

Note 1) Capacity is calculated at 220V for the 200V models and at 440V for the 400V models.

Note 2) Indicates the value when the PWM carrier frequency (parameter $\[\mathcal{L}\]$) is 2.5 kHz or less.

When low noise (PWM carrier frequency 8 kHz) is required at 18.5 kW or more, use an inverter of capacity one rank higher than the motor capacity.

Note 3) ±10% when the inverter is used continuously (load of 100%)

Note 4) Inverters, 18.5kW or greater, do not have wiring port covers. They have large openings, but there is no space to bend the external cables inside the unit. If they are fitted external to the cabinet, please use an optional wiring port cover.

Note 5) For 200V-55kW, 400V-90kW or larger model, be sure to install DC reactor.

However, this is unnecessary for DC input specifications.

Note 6) Three-phase 380~480V-50/60Hz for 4900PC Note 7) Complies with the European EMC Directive

DC Reactor

IEC/EN61800-3, 2nd environment, category C3

■ Common Specifications

		Item	Specification Specification
\top	Control syste	m	Sinusoidal PWM control
-	Output voltag	e adjustment	Main circuit voltage feedback control. (Switchable between automatic adjustment/ffx/control off)
	Output freque	ency range	Setting between 0.01 to 500Hz. Default max. frequency is set to 0.01 to 60Hz. Maximum frequency adjustment (30 to 500Hz)
	Minimum sett	ing steps of frequency	0.01Hz: operation panel input (60Hz base), 0.02Hz: analog input (60Hz base, 11 bit/0 to 10Vdc)
s -	Frequency ac	ccuracy	Within ±0.2% (25°C±10°C): analog input ±0.01% (25°C±10°C): digital input
ication	Voltage/frequ	ency characteristics	V/f constant, square reduction torque control, automatic torque boost, vector calculation control, base frequency adjustment 1, 2, 3, and 4 (25 to 500Hz), V/F 5-point arbitrary setting torque boost adjustment (0 to 30%), start frequency adjustment (0 to 10Hz), stop frequency adjustment (0 to 30Hz)
Control specifications	Frequency se	etting signal	$3k\Omega$ potentiometer (possible to connect to 1 to $10k\Omega$ -rated potentiometer) 0 to $10Vdc$ (input impedance Zin: $30k\Omega$) 0 to $\pm 10Vdc$ (Zin: $22k\Omega$) 4 to $20mAdc$ (Zin: $24k\Omega$)
	Terminal boar	rd base frequency	The characteristic can be set arbitrarily by two-point setting. Compliant with 6 types of input; analog input (RR, VI/II, RX, RX2), pulse input and binary/BCD input (*RX2, binary/BCD input: optional)
	Frequency jui		3 places. Setting of jump frequency and width.
		wer limit frequencies	Upper limit frequency: 0 to max. frequency, lower limit frequency: 0 to upper limit frequency
	PWM carrier	rrequency	200V-45kW or less, 400V-75kW or less : adjustable between 1.0 to 16kHz 200V-55kW or more, 400V-90kW or more : adjustable between 2.5 to 8kHz
- 1	PID control		Adjustment of proportional gain, integral time, differential time and delay filter
\dashv	Torque contro	ol .	Voltage command input specification: DC 0 to ±10V
	Acceleration/	deceleration time	0.01 to 6000 sec. Selectable from among acceleration/deceleration. times 1, 2, 3 and 4. Automatic acceleration/deceleration function. S-pattern acceleration/deceleration 1 and 2 pattern adjustable.
	DC braking		Adjustment of braking start frequency (0 to 120Hz), braking (0 to 100%) and braking time (0 to 10 sec.). With emergency stop braking function and motor shaft fix control function.
	Forward run/r	reverse run Note 1)	With F-CC closed to forward run, with R-CC closed to reverse run, with both closed to stop. With ST-CC opened to coast stop. Emergency stop by panel operation or terminal board.
	Jog run Note	1)	Jog mode, if selected, allows jog operation from the operation panel Jog run operation by terminal board is possible by setting the parameters.
Operation specifications	Preset speed	operation Note 1)	By changing the combination of open/close between S1, S2, S3, RR/S4-CC, set frequency + 15-speed operation. Selectable between acceleration/deceleration time, torque limit and V/f by set frequency.
	Retry		Capable of restarting after a check of the main circuit elements in case the protective function is activated. Max. 10 times selectable arbitrarily. Waiting time adjustment (0 to 10 sec
ds L	Soft stall		Automatic load reduction control at overloading. (Default: OFF)
ratio	Cooling fan C	N/OFF	The cooling fan will be stopped automatically to assure long life when unnecessary.
e Co	Operation panel key operation ON/OFF control		Key prohibition selectable between Stop key only, Mode key only, etc. All key operations can be prohibited.
- 1	Regenerative	power ride-through control	Possible to keep the motor running using its regenerative energy in case of a momentary power failure. (Default: OFF)
İ		power ride-through control	Possible to keep the motor running using its regenerative energy in case of a momentary power failure. (Default: OFF) Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF)
	Auto-restart o		
	Auto-restart of Simplified pat	pperation	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF)
	Auto-restart of Simplified pat Commercial i	pperation ttern operation	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load.
	Auto-restart of Simplified pat Commercial in Light-load hig Drooping fund	operation ttern operation nverter switching ph-speed operation ction	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance.
	Auto-restart of Simplified pat Commercial in Light-load hig	operation ttern operation nverter switching ph-speed operation ction	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value.
	Auto-restart of Simplified pat Commercial in Light-load hig Drooping fund	operation Itern operation nverter switching h-speed operation ottion	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance.
	Auto-restart of Simplified pat Commercial i Light-load hig Drooping func Override func	operation Itern operation nverter switching h-speed operation ottion	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload at dynamic braking
	Auto-restart of Simplified pat Commercial i Light-load hig Drooping func Override func	operation ttern operation nverter switching th-speed operation ction tion	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop
	Auto-restart of Simplified pat Commercial in Light-load high Drooping fund Override fund Protective fur Electronic the	operation ttern operation nverter switching th-speed operation ction tion	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level.
Protective function	Auto-restart of Simplified pat Commercial in Light-load high Drooping fund Override fund Protective fur Electronic the	operation terr operation nverter switching h-speed operation tition nction ermal characteristic	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop. Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit.
play functions Protective function	Auto-restart of Simplified pat Commercial in Light-load high Drooping fund Override fund Protective fur Electronic the	operation tern operation nverter switching th-speed operation ction tition hetion Alarms	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overforque), (motor
play full cuotis	Auto-restart of Simplified pat Commercial i Light-load hig Drooping fund Override func Protective fur Electronic the Reset 4-digit and 7-segment	peration Itern operation nverter switching his-speed operation Ition Iti	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source Side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at starting, overcurrent at starting, overcurrent on the load side at starting overcurrent on the load side, ground fault on the load side, inverter overload, (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The items in the parentheses are selectable. Operation frequency, operation frequency command, forw
play full cuotis	Auto-restart of Simplified pat Commercial i Light-load hig Drooping fund Override func Protective fur Electronic the Reset 4-digit and 7-segment	peration terro peration nverter switching th-speed operation ction ction ction ction ction ction ction definition ction	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overcitage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The Items in the parentheses are selectable. Operation frequency, operation frequen
play full cuotis	Auto-restart of Simplified pat Commercial i Light-load high Drooping fund Override funcional in Light-load high Protective fur Electronic the Reset 4-digit and 7-segment LED	peration terro peration moverter switching th-speed operation ction ctio	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, esting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, RAM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The items in the parentheses are selectable. Operation frequency, operation frequenc
Display fulcions Protective fulcifoli	Auto-restart of Simplified pat Commercial i Light-load high Drooping fund Override function of the Commercial in Light-load high Protective fur Electronic the Reset 4-digit and 7-segment LED	peration terr operation moretre switching th-speed operation totion totion and continue the con	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EFPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The items in the parentheses are selectable. Operation frequency, operation frequ
Display lancifolis	Auto-restart of Simplified pat Commercial i Light-load high Drooping fund Override funcional fun	peration terr operation nverter switching h-speed operation tition ettion Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display al input function	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload have fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side a
nputicinal put in constant in	Auto-restart of Simplified pat Commercial i Light-load high Drooping fund Override function of the Commercial in Light-load high Protective fur Electronic the Reset 4-digit and 7-segment LED	peration terro peration nverter switching th-speed operation ction ction ction Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display all input function aing	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EFPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The items in the parentheses are selectable. Operation frequency, operation frequ
Display Tunctions Protective function	Auto-restart of Simplified pat Commercial it Light-load high Drooping fund Override fund Protective fur Electronic the Reset 4-digit and 7-segment LED LED LED //output termin Source switch Failure detect	peration terro peration nverter switching th-speed operation ction ction ction Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display all input function aing	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operation gifficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source Side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at starting, overcurrent on the load side, ground fault on the load side, inverter overload, (motor overload), (output phase failure) The items in the parentheses are selectable. Operation frequency, operation frequency command, forward run/reverse run, output current, DC voltage, output voltage
Display functions Protective function	Auto-restart of Simplified pat Commercial i Light-load high prooping fund Override function of the Commercial in Light-load high prooping fund Override function of the Commercial in Light-load function	peration terro peration moverter switching th-speed operation ction ction ction ction	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload), (output phase failure) The Items in the parentheses are selectable. Operation frequency, operation frequ
Output signal iii d Display functions Protective function	Auto-restart of Simplified pat Commercial i Light-load high Drooping fund Override fun	peration terro peration moverter switching th-speed operation tition tition terrol peration te	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source of OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side. Dc circuit undervoltage, estiting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, estiting error, in retry, upper limit, lower limit. Operation frequency, operation frequency command, forward run/reverse run, output current, DC voltage, output voltage, compensated frequency,
Output signal Signal Display functions Protective function	Auto-restart of Simplified pat Commercial i Light-load high prooping fund Override fund Protective fur Electronic the Reset 4-digit and 7-segment LED LED LED LED LUD LUD LUD LUD	peration terro peration nverter switching ph-speed operation totion totion and claracteristic Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display hal input function ing ion signal de reach signal output interpretation terror of the peratical output interpretation inter	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current), (overtorque), (motor overload in provention, provention, provention, provention, provention, provention, provention, provention, proventi
Output signal Display functions Protective function	Auto-restart of Simplified pat Commercial i Light-load high prooping fund Override fund Protective fur Electronic the Reset 4-digit and 7-segment LED LED LED LED LUD LUD LUD LUD	peration terro peration merter switching jh-speed operation totion totion mettion Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display all input function ing ion signal ed reach signal output Note 2) mit frequency signal output uency meter/output for ammeter	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoltage, short circuit on the load side, ground fault on the load side (Note 5), undervoltage, momentary power failure (15ms or more) non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Sees by 1s contact closed (or 1b contact operacle) or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoltage on power source side, DC circuit undervoltage, setting error, in retry, upper limit, lower limit. Overcurrent, overvoltage, fin overheat, short circuit on the load side, ground fault on the load side, inverter overload, arm overcurrent at starting, overcurrent on the load side at sta EEPROM error, RAM error, ROM error, transmission error, (dynamic braking resistor overcurrent/overload), (emergency stop), (undervoltage), (low current, on the load side at stall prevention frequency operation free pency operation frequency operation frequency operation frequency operation frequency operation frequency operation fr
Output signal iii d Display functions Protective function	Auto-restart of Simplified pat Commercial it Light-load high prooping fund Override funcional it Light-load high prooping fund Override funcional it Light-load high prooping fund Override funcional in Light-load high prooping funding funcional in Light-load high prooping funcional in Light-load funcional in Light-loa	peration terro peration neverter switching th-speed operation ction ctio	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency, Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoitage, short circuit on the load side, ground fault on the load side (Note 5), undervoitage, momentary power failure (15ms or more non-stop control at momentary power failure, overcurrent on the load side at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1s contact closed (or 1b contact opened), or by operation panel. Or power source OFF/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F/ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, un
Output signal iii d Display functions Protective function	Auto-restart of Simplified pat Commercial it Light-load high Drooping fund Override fund Protective fur Electronic the Reset 4-digit and 7-segment LED LED //output termin source switch Failure detect Low speed/spe Upper/lower lin Note 2) Output for freq Note 3) Pulse train freq munication fund Operating env. Ambient temps Ambient Ambient temps Ambient Ambien	peration terro peration moverter switching th-speed operation ction ctio	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency, Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter Increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoitage, short circuit on the load side, ground fault on the load side (Note 5), undervoitage, momentary power failure (15ms or more non-stop control at momentary power failure, overload protection, arm overload at starting, overcurrent and overload at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1a contact closed (or 1b contact opened), or by operation panel. Or power source OFFON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of FON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of FON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of FON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of FON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, un
ronments Output signal Unit of the Control output signal Unit outp	Auto-restart of Simplified pat Commercial it Light-load high prooping fund Override funcional it Light-load high prooping fund Override funcional it Light-load high prooping fund Override funcional in Light-load high prooping funding funcional in Light-load high prooping funcional in Light-load funcional in Light-loa	peration terri operation inverter switching jh-speed operation tition tition and tition Alarms Causes of failures Monitoring function Free unit display Automatic edit function User default setting Charge display all input function ing ion signal ed reach signal output Note 2) mit frequency signal output uency meter/output for ammeter squency output ivironments iverature erature	Possible to restart the motor in coasting in accordance with its speed and direction. (Default: OFF) Possible to select each 8 patterns in 2 groups from 15-speed operation frequency. Max. 16 types of operation possible. Terminal board operation/repeat operation possible. Possible to switch operation by commercial power source or inverter increases the operating efficiency of the machine by increasing the rotational speed of the motor when it is operated under light load. When two or more inverters are used to operate a single load, this function prevents load from concentrating on one inverter due to unbalance. External input signal adjustment is possible to the operation frequency command value. Stall prevention, current limit, overcurrent, overvoitage, short circuit on the load side, ground fault on the load side (Note 5), undervoitage, momentary power failure (15ms or more) non-stop control at momentary power failure, overcurrent on the load side at starting, overcurrent and overfoad at dynamic braking resistance, fin overheat, emergency stop Switchable between standard motor/constant torque VF motor, adjustment of overload protection and stall prevention level. Reset by 1s contact closed (or 1b contact opened), or by operation panel. Or power source OFF(ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F(ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F(ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage on power source of F(ON. This function is also used to save and clear trip records. Stall prevention during operation, overload limit, overload, undervoitage, or netry, undervoitage, ore

Note 1) 16 contact input terminals (of which 8 are options) are programmable contact input terminals, and they make it possible to arbitrarily select from 136 types of signals.

Note 2) Programmable ON/OFF output terminals make it possible to arbitrarily select from 150 types of signals.


Note 3) Programmable analog output terminals make it possible to arbitrarily select from 55 types of signals.


Note 4) When using inverters where the ambient temperature will rise above 50°C, remove the upper cover and operate each inverter at a current lower than the rated one.


Note 5) This function protects inverters from overcurrent due to output circuit ground fault.


External dimensions


■ 200 V class - 0.4 to 55 kW, 400 V class -0.75 to 90 kW model



























put Voltage	Applicable Motor	Inverter Type		Din	nensions (r	nm)		External Dimension	Approx. Weight
Class	(kW)	inverter type	W	Н	D	W1	H1	Drawing	(kg)
	0.4	VFAS1-2004PL							3
	0.75	VFAS1-2007PL	130	230	152	114	220	A	3
	1.5	VFAS1-2015PL							3
	2.2	VFAS1-2022PL	155	260	164	138	249	В	4
	3.7/4.0	VFAS1-2037PL	155	260	104	130	249	P [4
	5.5	VFAS1-2055PL	175	295	164	158	283	С	5.5
	7.5	VFAS1-2075PL	210	295	191	190	283	D	7.5
200V	11	VFAS1-2110PM	230	400	191	210	386	-	14
	15	VFAS1-2150PM	230	400	191	210	300	E	14
	18.5	VFAS1-2185PM	240	420	212	206	403	-	21
	22	VFAS1-2220PM	240	420	212	200	403	F	21
	30	VFAS1-2300PM							41
	37	VFAS1-2370PM	320	550	242	280	525	Н	41
	45	VFAS1-2450PM	1						41
	55	VFAS1-2550P	310	680 (920)	370	250	650	J (J')	59 (87)
	0.75	VFAS1-4007PL							3
	1.5	VFAS1-4015PL	130	230	152	114	220	A	3
	2.2	VFAS1-4022PL							3
	3.7/4.0	VFAS1-4037PL	155	260	164	138	249	В	4
	5.5	VFAS1-4055PL	175	295	164	158	283	_	5.5
	7.5	VFAS1-4075PL	1/5	295	164	138	263	C	5.5
	11	VFAS1-4110PL	210	295	191	190	283	D	8
100) (15	VFAS1-4150PL	000	400	404	040	386	-	13
400V	18.5	VFAS1-4185PL	230	400	191	210	386	E	16
	22	VFAS1-4220PL	240	420	212	206	403	F	21
	30	VFAS1-4300PL	040	FFO	040	000	F00		29
	37	VFAS1-4370PL	240	550	242	206	529	G	29
	45	VFAS1-4450PL							48
	55	VFAS1-4550PL	320	630	290	280	605	I	48
	75	VFAS1-4750PL				280	605		48
	90	VFAS1-4900PC	310	680 (920)	370	250	650	J (J')	59 (89)


Note) Value in () includes attached DC reactor.


3


External dimensions


■ 200 V class - 75 kW, 400 V class - 110 to 500 kW model


























Input Voltage		Inverter Type				Dime	ensions (mm)				External Dimension	Approx. Weight
Class	(kW)	inverter type	W	Н	D	W1	H1	W2	H2	НЗ	H4	Drawing	(kg)
200V	75	VFAS1-2750P	350	782 (1022)	370	298	758	360	72	150	30	K (K')	72 (103)
	110	VFAS1-4110KPC	350	782 (1022)	370	298	758	360	72	150	30	K (K')	74 (108)
	132	VFAS1-4132KPC	330	950 (1190)	370	285	920	340	75	150	30	L (L')	82 (118)
400V	160	VFAS1-4160KPC	430	950 (1190)	370	350	920	440	75	150	30	M (M')	104 (161)
	200	VFAS1-4200KPC		050	370	540	920	595	75	150	30	N	134 (194)
	220	VFAS1-4220KPC	585	950 (1190)								(N')	136
	280	VFAS1-4280KPC		(1190)								(14)	(204)
	355	VFAS1-4355KPC	880	1150	370	440	4400	890		450		(01)	260
	400	VFAS1-4400KPC	880	(1390)	370	418	1120	890	75 _	150	30	(O')	(370)
	500	VFAS1-4500KPC	1108	1150 (1390)	370	533	1120	1120	75	150	30	(P')	330 (462)

Note) Value in () includes attached DC reactor .

5

Standard connection diagrams

Standard connection diagram : Sink logic (common : CC)


Standard connection diagram : Source logic (common : P24)

Main circuit power supply


200V class:

0.4~75kW 3-phase, 200 to 240V-50/60Hz 400V class: 0.75 to 90kW 3-phase, 380 to 240V-50/60Hz


110 to 500kW 3-phase, 380 to 440V-50Hz 3-phase, 380 to 480V-60Hz



ړ ⊘----⊘ې



SOURCE: SINK



Ammeter or voltmeter External potentiomete (or voltage signal between RR/S4 and CCA:0~10V)

*5

i-@----@-

Preset speed 1 Preset speed 2

Voltage signal:0~10V or curent signal:4(0)~20mA

*1: The inverter is shipped with the terminals PO and PA/+ shorted with a bar (200V-45kW or amaller, 400V-75kW or smaller).

Remove this shorting bar when installing a DC reactor (DCL). For 200V-55kW or more, and 400V-90kW or more models, be sure to install the DC rector. *2: The DC reactor is built in for models 200V-11kW~45kW and 400V-18.5kW~75kW.

*3: The noise filter is built in for models 200V-45kW or smaller and all of 400V.

*4: External braking resistor (option). Dynamic braking drive circuit built-in (GTR7)as standard for models 160kW or smaller.

*5: Power generation braking Unit (option).when the external braking resistor (optional) is used on 200kW or more models, the separate power braking unit (optional) is required.

*6: To supply a DC power, connect the cables to the PA/+ and PA/- terminals.


*7: If want to use DC power supply to operate the inverter (200V: 18.5kW or more, 400V: 22kW or more), be sure to contact your supplier customer support center, because an inrush current limiting circuit is required in such a case.

*8: For models 200V-75kW and 400V-110kW or larger, three-phase power input is necessary to drive the fan if you want to use a DC power supply.

*9: The functions assigned to terminals OUT1. VI/II and RR/S4 can be swiched by changing parameter settings. *10: To supply control power from an external power supply for backing up the control power supplled from the inverter. an

optional control power backup device (CPS002Z) is required, Insuch a case, the backup device is used at the same time with the internal power supply of the inverter. The optional control power backup unit can be used with both 200V and 400V models.

*11: The rating of 400V-355 to 500kW have the double terminals of R/L1, S/L2, T/L3 for power input, and PO for DC reactor. Please refer the following figure for the wiring.



Terminal functions

Main circuit terminal

- Main Circuit te	a miniqu
Terminal Symbol	Terminal Function
(Grounding terminal for inverter casing
R/L1, S/L2, T/L3	200V class: 0.4~75kW Three-phase 200~240V-50/60Hz 0.75~90kW Three-phase 380~480V-50/60Hz 110~500kW Three-phase 380~440V-50Hz Three-phase 380~480V-60Hz (355 to 500kW have the double terminals
U/T1, V/T2, W/T3	Connect to a (3-phase induction) motor.
PA/+, PB	Connect a braking resistor. (For the optional dynamic braking unit, connect it between PA/+ and PC/) Change the parameters Pb, Pbr and PbCP if necessary. 200kW models and smaller are not equipped with terminal PB. If your are using such a model and you wish to use a braking resistor, you will need to purchase a braking unit separately.
PC/-	This is a negative potential terminal in the internal DC main circuit. DC common power can be input across the PA/+ terminals (positive potential).
PO, PA/+	Terminals for connecting a DC reactor (DCL: optional external device). Shorted by a short bar when shipped from the factory (200V: 45kW or smaller, 400V: 75kW or smaller). Before installing DCL, remove the short bar. (355 to 500kW have the double terminals of PO)
RO, SO, TO	200V class: 75kW 400V class:110kW~500kW Inverter's cooling power input terminals. When using a DC power supply, connect three-phase power cables.

■ Control	circuit	ter	rminal The terminal function set	tings can be changed according to the application
Terminal Symbol	Input/output	Fu	nction	Electrical Specifications
F	Input	input	Shorting across F-CC causes forward rotation; open causes deceleration stop. (Across ST-CC is short state.)	Voltage free contact input 24Vdc-5mA or less
R	Input	contact input	Shorting across R-CC causes reverse rotation; open causes deceleration stop. (Across ST-CC is short state.)	Lan current signal. Choose low current contacts to avoid poor attaching.
RES	Input	programmable	Shorting and then opening RES-CC cancels the status held by an inverter protective function. When the inverter is operating normally, shorting and then opening RES-CC produces no effect.	* Sink/source selectable with SW1 Sink input ON : Less than DC10V OFF : DC16V or more OFF : Less than DC5V
S1	Input	rogi	Shorting across S1-CC causes preset speed operation.	Note:
S2	Input	ion	Shorting across S2-CC causes preset speed operation.	Even when an external power supply is used (in sink logic mode, i.e., when SINK (PLC) is selected), connect the
S3	Input	funct	Shorting across S3-CC causes preset speed operation.	reference potential-side (0V side) cable from the power supply
RR/S4	Input	Multifunction	SW3: When SW4 is in the S4 position, S4 and CC are shorted and preset speed operation is selected.	to the CC terminal.
P24/PLC	Output		dc power output (when SW1 is in any position other than PLC) internal output terminal	24Vdc-200mA
1 24/1 20	Input		V1 is turned to the PLC position, this terminal can be used as a common terminal when an rnal power supply is used.	-
CC*1	Common to input/output		tal signal equipotential (0V) terminal for the control circuit and equipotential (0V) terminal in optional control power supply backup.	_
PP	Output		log input setting power output	10Vdc (Permissible load current:10mAdc)
PWR*2	Input	betw This It is	24/PLC and PWR are short-circuited, the motor is put into a standby state. And if the circuit ween them is opened, the motor coasts and stops. These terminals can be used for interlock. terminal is not a multifunction programmable input terminal. a terminal with the power removal safety function that complies with EN954-1 category 3 IEC/EN61508-1 SIL II.	Regardless of the setting of SW1 ON: DC17V or more OFF: Less than DC2V (OFF: Coast stop)
RR/S4	Input		3: Multifunction programmable analog input terminal when SW4 is in the RR position.	10Vdc (Internal impedance:30 kΩ)
VI/I I	Input	freq	ifunction programmable analog input.Standard default setting: 0~10Vdc input and 0~60Hz uency. This terminal can also be used as a 4-20mAdc (0-20mAdc) input terminal, if the uneter F 10B set to 1.	10Vdc (Internal impedance:30 k Ω) 4~20mA (Internal impedance:242 Ω)
RX	Input		ifunction programmable analog input. Standard default setting:0~±10Vdc input and 60Hz frequency.	10Vdc (Internal impedance:22 kΩ)
FM	Output	Con This	ifunction programmable analog output. Standard default setting: output frequency nect a 1mAdc full-scale ammeter or 7.5Vdc (10Vdc)-1mA full-scale voltmeter. terminal can also be used as a 0-20mAdc (4-20mA) terminal, if the parameter F 58 I set to d the SW2 switch is set to OFF.	1mA full-scale DC ammeter or 7.5Vdc-1mA full-scale DC voltmeter 0-20mA (4-20mA) Full-scale DC ammeter
AM	Output	Use	ifunction programmable analog output. Standard default setting: output current this terminal to connect a 1mAdc full-scale ammeter or 7.5Vdc (10Vdc)-1mA full-scale meter.	1mA full-scale DC ammeter or 7.5Vdc-1mA full-scale DC voltmeter
OUT1	Output	outp	ifunction programmable open collector output. The default setting is to output a signal when ut low speed threshold has been reached. Depending on the SW4 setting, pulses are ut with frequencies of 1.00kHz to 43.20kHz. Standard default setting:3.84kHz	Open collector output 24Vdc-50mA
OUT2] '		ifunction programmable open collector output. By default, it is set to output a signal cating the completion of acceleration or deceleration.	*Sink logic/source logic switchable
NO	Common to	_	al output signal equipotential (0V) terminal for the control circuit. It is insulated from the CC terminal.	
CCA*1	Common to input/output		log input/output signal equipotential (0V) terminal for the control circuit.	-
+SU	Input		power input terminal for operating the control circuit. Connect a control power backup ce (optional) between +SU and CC.	Voltage:24Vdc±10% Use a power supply with a current rating of 1.1A or more.
FLA FLB FLC	Output	Use	ay contact output. Contact rating d to detect the activation of the inverter's protective function. Contact across FLA-FLC is ed and FLB-FLC is opened during protection function operation.	250Vac-2A 30Vdc-1A :at resistance load 250Vac-1A

*1: Although the CC terminal and the CCA terminal are not insulated, they should be used separately, one for the logic circuit and the other for the analog circuit.
*2: The PWR terminal is not the same as the ST (standby signal input) terminal provided for conventional models. To use the ST function, assign it to a multifunction terminal (F, R, RES or S1 to S4) that is not currently in use. Example: When assigning the ST function to the S3 terminal.

Set FIID to D, and Set FII7 to 5. These settings put the motor into a standby state if S3 and CC are short-circuited, or coast and stop the motor if the circuit between S3 and CC is opened.

For inverter users

When studying how to use our inverters

Notes

Leakage current

This inverter uses high-speed switching devices for PWM control.


When a relatively long cable is used for power supply to an inverter, current may leak from the cable or the motor to the ground because of its capacitance, adversely affecting peripheral equipment. The intensity of such a leakage current depends on the PWM carrier frequency, the lengths of the input and output cables, etc., of the inverter. To prevent current leakage, it is recommended to take the following

[Effects of leakage current]

Leakage current which increases when an inverter is used may pass through the following routes:

- Route (1) ... Leakage due to the capacitance between the ground and the noise filter
- Route (2) ... Leakage due to the capacitance between the ground and the inverter Route (3) ... Leakage due to the capacitance between ground and the cable connecting
- the inverter and the motor

 Route (4) ... Leakage due to the capacitance of the cable connecting the motor and an inverter in
- another power distribution line
 Route (5) ... Leakage through the grounding line common to motors
- Route (6) ... Leakage to another line because of the capacitance of the ground Leakage current which passes through the above routes may cause the following trouble
- Malfunction of a leakage circuit breaker in the same or another power distribution line
- Malfunction of a ground-relay installed in the same or another power distribution line
- Noise produced at the output of an electronic device in another power distribution line
- Activation of an external thermal relay installed between the inverter and the motor, at a current below the rate current



[Measures against effects of leakage current]

The measures against the effects of leakage current are as follows:

1) Measures to prevent the malfunction of leakage circuit breakers

- (1) Decrease the PWM carrier frequency of the inverter. Note)
- (2) Use radio-frequency interference-proof ELCBs as ground-fault interrupters in not only the system into which the inverter is incorporated but also other systems. When ELCBs are used, the PWM carrier frequency needs to be increased to operate the inverter.
- (3) When connecting multiple inverters to a single ELCB, use an ELCB with a high current sensitivity or reduce the number of inverters connected to the ELCB.
- 2) Measures against malfunction of ground-fault relay:
- (1) Decrease the PWM carrier frequency of the inverter. Note)
- (2) Install ground-fault relays with a high-frequency protective function (e.g., Toshiba CCR12 type of relays) in both the same and other lines. When ELCBs are used, the PWM carrier frequency needs to be increased to operate the inverter
- 3) Measures against noise produced by other electric and electronic systems:(1) Separate the grounding line of the inverter from that of the affected electric
- (2) Decrease the PWM carrier frequency of the inverter. Note)
- 4) Measures against malfunction of external thermal relays:
- (1) Remove the external thermal relay and use the electronic thermal function of the inverter instead of it. (Unapplicable to cases where a single inverter is used to drive more than one motor. Refer to the instruction manual for measures to be taken when thermal relays cannot be removed.)
- (2) Decrease the PWM carrier frequency of the inverter. Note)
- 5) Measures by means of wiring and grounding

and electronic systems.

- (1) Use a grounding wire as large as possible.
- (2) Separate the inverter's grounding wire from that of other systems or install the grounding wire of each system separately to the grounding point.
- (3) Ground (shield) the main circuit wires with metallic conduits.
- (4) Use the shortest possible cables to connect the inverter to the motor

(5) If the inverter has a high-attenuation EMI filter, turn off the grounding capacitor detachment switch to reduce the leakage current. Note that doing so leads to a reduction in the noise attenuating effect.

Note) In the case of this inverter, the PWM carrier frequency can be decreased to 1.0kHz.

However, that it should not be set to less than 2.0kHz during vector control.

Decreasing the carrier frequency results in an increase in electromagnetic noise from the motor.

Ground fault

Before begining operation, thoroughly check the wiring between the motor and the inverter for incorrect wiring or short circuits. Do not ground the neutral point of any star-connected motor.

Radio interference

[Noise produced by inverters]

Since this inverter performs PWM control, it produces noise and sometimes affects nearby instrumental devices, electrical and electronic systems, etc. The effects of noise greatly vary with the noise resistance of each individual device, its wiring condition, the distance between it and the inverter, etc.


[Measures against noises]

According to the route through which noise is transmitted, the noises produced by an inverter are classified into transmission noise, induction noise and radiation noise.

[Examples of protective measures]

- Separate the power line from other lines, such as weak-current lines and signal lines, and install them apart from each other.
- Install a noise filter in each inverter. It is effective for noise prevention to install noise filters in other devices and systems, as well.
- Shield cables and wires with grounded metallic conduits, and cover electronic systems with grounded metallic cases.
- Separate the power distribution line of the inverter from that of other devices and systems.
- Install the input and output cables of the inverter apart from each other.
- Use shielded twisted pair wires for wiring of the weak-current and signal circuits, and always ground one of each pair of wires.
- Ground the inverter with grounding wires as large and short as possible separately from other devices and systems.

On 200V 0.4 to 7.5kW and 400V 0.75kW to 500kW models, noise can be greatly reduced as they have a built-in EMI noise filter on their input side.



Power factor improvement capacitors

Do not install a power factor improvement capacitors on the input or output side of the inverter.

Installing a power factor improvement capacitor on the input or output side causes current containing harmonic components to flow into the capacitor, adversely affecting the capacitor itself or causing the inverter to trip. To improve the power factor, install an input AC reactor or a DC reactor (optional) on the primary side of the inverter.

Installation of input AC rectors

These devices are used to improve the input power factor and suppress high harmonic currents and surges. Install an input AC reactor when using this inverter under the following conditions:

- (1) When the power source capacity is 500kVA or more, and when it is 10 times or more greater than the inverter capacity.
- (2) When the inverter is connected the same power distribution system as a thyristor-committed control equipment.
- (3) When the inverter is connected to the same power distribution system as that of distorted wave-producing systems, such as arc furnaces and large-capacity inverters.

When wiring the inverter

Wiring precautions

Installing a molded-case circuit breaker [MCCB]

- (1) Install a molded-case circuit breaker (MCCB) on the inverter's power supply input to protect the wiring.
- (2) Avoid turning the molded-case circuit breaker on and off frequently to turn on/off the motor.
- (3) To turn on/off the motor frequently, close/break the control terminals F (or R)-

Installing a magnetic contactor [MC] [primary side]

- (1) To prevent an automatic restart after the power interruption or overload relay has tripped, or actuation of the protective circuit, install an electro-magnetic contact in the power supply.
- (2) The inverter is provided with a failure detection relay (FL), so that, if its contacts are connected to the operation circuit of the magnetic contactor on the primary side, the magnetic contactor will be opened when the protective circuit of the inverter is activated.
- (3) The inverter can be used without a magnetic contactor. In this case, use an MCCB (equipped with a voltage tripping device) for opening the primary circuit when the inverter protective circuit is activated.
- (4) Avoid turning the magnetic contactor on and off frequently to turn on/off the
- (5) To turn on/off the motor frequently, close/break the control terminals F (or R)-CC.

Installing a magnetic contactor [MC] [secondary side]

- (1) As a rule, if a magnetic contactor is installed between the inverter and the motor, do not turn of ON/OFF while running. (If the secondary-side contactor is turned of ON/OFF while running, a large current may flow in the inverter, causing inverter damage and failure.)
- (2) A magnetic contactor may be installed to change the motor or change to the commercial power source when the inverter is stopped. Always use an interlock with the magnetic contactor in this situation so that the commercial power supply is not applied to the inverter's output terminals.

External signal

- (1) Use a relay rated for low currents. Mount a surge suppressor on the excitation coil of the relay.
- (2) When wiring the control circuit, use shielded wires or twisted pair cables.
- (3) Because all of the control terminals except FLA, FLB and FLC are connected to electronic circuits, insulate these terminals to prevent them from coming into contact with the main circuit.

Installing an overload relay

- (1) The inverter has an electronic-thermal overload protective function. However, in the following cases, the thermal relay operation level must be adjusted or an overload relay matching the motor's characteristics must be installed between the inverter and the motor.
- (a) When using a motor having a rated current value different from that of the equivalent.
- (b) When driving several motors simultaneously.
- (2) When using the inverter to control the operation of a constant-torque motor (VF motor), change the protective characteristic of the electronic thermal relay according to the setting of the VF motor.
- (3) In order to adequately protect a motor used for low-speed operation, we recommend the use of a motor equipped with a embedded thermal relay.

When changing the motor speed

Application to standard motors

Vibratio

When a motor is operated with an industrial inverter, it experiences more vibrations than when it is operated by the commercial power supply. The vibration can be reduced to a negligible level by securing the motor and machine to the base firmly. If the base is weak, however, the vibration may increase at a light load due to resonance with the mechanical system.

Reduction gear, belt, chain

Note that the lubrication capability of a reducer or a converter used as the interface of the motor and the load machine may affected at low speeds.

When operating at a frequencies exceeding 60 Hz or higher, power transmission mechanisms such as reduction gear, belts and chains, may cause problems such as production of noise, a reduction in strength, or shortening of service life.


Frequency

Before setting the maximum frequency to 60 Hz or higher, confirm that this operating range is acceptable for the motor.

Application to special motors

Braking moto

When using a braking motor, if the braking circuit is directly connected to the inverters's output terminals, the brake cannot be released because of the lowered starting voltage. Therefore, when using a braking motor, connect the braking circuit to the inverter's power supply side, as shown on the below. Usually, braking motors produce larger noise in low speed ranges.



Gear motor

When using an industrial inverter to drive a gear motor, inquire of the motor manufacturer about its continuous operation range, since low-speed operation of a gear motor may cause insufficient lubrication.

Toshiba Gold Motor (High-efficiency power-saving motor)

Inverter-driven operation of Toshiba Gold Motors is the best solution for saving energy. This is because these motors have improved efficiency, power factor, and noise/vibration reduction characteristics when compared to standard motors.

Pole-changing motor

Pole-changing motors can be driven by this inverter. Before changing poles, however, be sure to let the motor come to a complete stop.

Hight-pole-count motors

Note that hight-pole count motors(8 or more poles), which may be used for fans,etc., have higher rated current than 4-pole moters.

The current ratings of multipole motors are relatively high. So, when selecting an inverter, you must pay special attention to its current rating so that the current rating of the motor is below that of the inverter.

Single-phase motor

Because single-phase motors are equipped with a centrifugal switch and capacitors for starting, they cannot be driven by an inverter. If only a single-phase, power system is available a 3-phase motor can be driven by using a single-phase input interter to convert it into a 3-phase 200V output. (A special inverter and a 3-phase

For inverter users

Selecting peripheral and wiring sizes devices

Malhama	Applicable		Input cu	rrent (A)	Molded-ca breaker Note	ase circuit (MCCB) 1),2)	Mag contac Note 1	netic tor (MC) (,3),4),5)					Wire Note	size 6),7)					Inverter Screv No	Terminal w Size te 8)
Voltage Class	Motor (kW)		mpat ca					ational ent (A) C1	Input to	Main erminal S, T)	circuit Output t (U, V	terminal /, W)	DC te		Braking Braking uni Not	resistor/ t (optional) e 9)	Groun		Main Circuit	GND
			Without Reactor	With Reactor	Without Reactor	With Reactor	Without Reactor	With Reactor	AWG	mm²	AWG	mm²	AWG	mm²	AWG	mm²	AWG	mm²	Terminal	Terminal
	0.4	VFAS1-2004PL	3.5	2.1	5	5	25	25	14	1.5	14	1.5	14	1.5	14	1.5	14	2.5		
	0.75	VFAS1-2007PL	6.1	3.2	10	5	25	25	14	1.5	14	1.5	14	1.5	14	1.5	14	2.5		
	1.5	VFAS1-2015PL	11.5	6.4	15	10	25	25	14	1.5	14	1.5	12	1.5	14	1.5	14	2.5	M4	
	2.2	VFAS1-2022PL	15	9.3	20	15	25	25	12	1.5	12	1.5	10	2.5	14	1.5	14	2.5		
	3.7/4.0	VFAS1-2037PL	26	15.5	30	30	32	25	10	4	10	4	8	6	14	1.5	12	4		
	5.5	VFAS1-2055PL	35	22.5	50	40	40	25	8	6	8	6	6	10	14	1.5	10	6		
	7.5	VFAS1-2075PL	45	34.5	60	40	50	40	8	10	8	10	4	16	12	2.5	10	10	M5	M5
0001/	11	VFAS1-2110PM	-	53.5	-	75	-	80	4	16	4	16	3	16	10	4	10	16		1
200V	15	VFAS1-2150PM	-	72	-	100	-	80	4	25	4	25	1	25	8	6	10	16	M6	
	18.5	VFAS1-2185PM	-	77	-	100	-	80	3	25	3	25	1/0	35	8	10	8	16		1
	22	VFAS1-2220PM	-	88	-	125	-	125	2	25	2	25	2/0	35	6	16	8	16	M8	
	30	VFAS1-2300PM	-	125	-	150	-	125	2/0	50	2/0	50	4/0	70	4	25	6	25		
	37	VFAS1-2370PM	-	140	-	175	-	250	3/0	70	3/0	70	250MCM	95	3	35	6	35	1	M8
	45	VFAS1-2450PM	-	165	-	200	-	250	4/0	70	4/0	70	300MCM	95	2	50	6	35	M12	
	55	VFAS1-2550P	-	200	-	250	-	275	3/0×2	70×2	3/0×2	120	4/0×2	95×2	1/0	50	2	70	Note 13)	
	75	VFAS1-2750P	-	270	-	350	-	350	4/0×2	95×2	250MCM×2	70×2	300MCM×2	120×2	1/0	35×2	2	95	1	M10
	0.75	VFAS1-4007PL	3.7	2.1	5	4	25	25	14	1.5	14	1.5	14	1.5	14	1.5	14	2.5	-	
	1.5	VFAS1-4015PL	5.8	3.8	10	6.3	25	25	14	1.5	14	1.5	14	1.5	14	1.5	14	2.5	1	
	2.2	VFAS1-4022PL	8.2	5.7	14	10	25	25	14	1.5	14	1.5	14	1.5	14	1.5	14	2.5	M4	1
	3.7/4.0	VFAS1-4037PL	14	8.7	18	14	25	25	12	1.5	12	1.5	10	2.5	14	1.5	14	2.5	1	
	5.5	VFAS1-4055PL	20.5	12.7	32	25	25	25	10	2.5	10	2.5	8	4	14	1.5	12	2.5	1	
	7.5	VFAS1-4075PL	27	16.3	32	25	32	25	10	4	10	4	8	6	14	1.5	12	4		1
	11	VFAS1-4110PL	36.5	21.5	50	30	40	32	8	6	8	6	6	10	14	1.5	10	6	M5	M5
	15	VFAS1-4150PL	48	33.5	60	40	50	40	6	10	6	10	4	16	12	2.5	10	10		1
	18.5	VFAS1-4185PL	-	45.5	-	60	-	50	6	10	6	10	4	16	10	2.5	10	10	M6	
	22	VFAS1-4220PL	-	50	-	60	-	50	6	10	6	10	4	16	10	4	10	10		1
	30	VFAS1-4300PL	-	66	-	100	-	80	4	16	4	16	2	25	8	6	10	16	M8	
	37	VFAS1-4370PL	-	84	-	100	-	125	3	25	3	25	1	35	8	10	8	16	1	
	45	VFAS1-4450PL	-	105	-	125	-	125	1	35	1	35	2/0	50	6	16	8	16		
	55	VFAS1-4550PL	-	120	-	150	-	125	1/0	50	1/0	50	3/0	70	6	16	6	25	1	M8
400V	75	VFAS1-4750PL	-	165	-	200	-	250	3/0	70	3/0	70	250MCM	95	3	35	6	35	M12	
	90	VFAS1-4900PC	-	170	-	200	-	250	1/0×2	70×2	1/0×2	95	1/0×2	95×2	1/0	35	2	70	Note 13)	
	110	VFAS1-4110KPC	-	200	-	250	-	275	3/0×2	95×2	3/0×2	120	2/0×2	120×2	1/0	50	2	95	1 ~	M10
	132	VFAS1-4132KPC	-	240	-	300	-	315	4/0×2	95×2	4/0×2	150	4/0×2	120×2	4/0	70	1/0	95	1	
	160	VFAS1-4160KPC	-	290	-	350	-	350	300MCM×2	120×2	300MCM×2		350MCM×2	150×2	4/0	95	1/0	120		
	200	VFAS1-4200KPC	-	360	-	500	-	500	4/0×3	150×2	4/0×3	120×2	3/0×3	150×3	300MCM	150	1/0	150	1	
	220	VFAS1-4220KPC	-	395	-	500	-	500	250MCM×3	150×3	250MCM×3		4/0×3	150×3	300MCM	150	2/0	150	1	
	280	VFAS1-4280KPC	-	495	-	700	-	700	350MCM×3	150×3	350MCM×3	185×2	300MCM×3	150×4	300MCM	150	3/0	120×2	1	
	355	VFAS1-4355KPC	-	637	-	1000	-	1000	400MCM×2×2 Note 12)		400MCM×4	150×3	500MCM×3	185×4	350MCM×2	185×2	4/0	120×2	M12	M12
	400	VFAS1-4400KPC	-	709	-	1000	-	1000	500MCM×2×2 Note 12)	150×2×2 Note 12)	500MCM×4	185×3	500MCM×4	185×4 Note 11)	350MCM×2	185×2	4/0	150×2	1	
	500	VFAS1-4500KPC	-	876	-	1200	-	1600	400MCM ×3×2 Note 12)	150×3×2 Note 12)	400MCM×5	185×4	500MCM×4	180×4 Note 11)	350MCM×2	185×2	250MCM	150×2		

Note 1) Selections for use of the Toshiba 4-pole standard motor with power supply voltage of 200V/400V-50Hz.

Note 2) Choose the MCCB according to the power supply capacity.

For comply with UL and CSA standard, use the fuse certified by UL and CSA.

Note 3) When the motor is driven by commercial power supply switching, for example, use an electromagnetic contactor that is matched to AC-3 class motor rated current.

Note 4) Attach surge killers to the magnetic contactor and exciting coil of the relay.

Note 5) In the case the magnetic contactor (MC) with 2a-type auxiliary contacts is used for the control circuit, raise the reliability of the contact by using 2a-type contacts in parallel connection.

Note 6) The recommended cable size is that of the cable (e.g. 600V class, HIV cable) with continuous maximum permissible temperature of 75°C. Ambient temperature is 40°C or less and the wiring distance is 30m or less.

Note 7) For the control circuit, use shielded wires whose size (cross-section) is 0.75 mm2 or more.

Note 8) The screw size of the control terminals is M3.

Note 9) Choose the wiring size according to the braking resistor value.

Note 10) On 200 V class 55 kW or more, and 400 V class 90 kW or more models, be sure to install the DC reactor.

Note 11) The recommended cable is 600V class HIV cable with permissible temperature of 90°C.

Note 12) The number refers to a cable composition. For example, in the case of "150 × 2 × 2". 150 × 2 × 2 — Number of cables connected in parallel on the terminal board ---- Number of cables connected to each terminal board

Note 13) The screw sizes of terminal R/L1, S/L2, T/L3, U/T1, V/T2, and W/T3, for VFAS1-2500~2750P, 4900~4132KPC are M10.

Selecting the Capacity (model) of the Inverter

(selection)

Refer to the applicable motor capacities listed in the standard specifications. When driving a high-pole motor, special motor, or multiple motors in parallel, select such an inverter that the sum of the motor rated current multiplied by 1.05 to 1.1 is less than the inverter's rated output current value.

Acceleration/deceleration times

The actual acceleration and deceleration times of a motor driven by an inverter are determined by the torque and moment of inertia2 of the load, and can be calculated by the following equations. The acceleration and deceleration times of an inverter can be set individually. In any case, however, they should be set longer than their respective values determined by the following equations.

,	3 4
Acceleration time	$ta = \frac{(JM+JL) \times \Delta N}{9.56 \times (TM-TL)} \text{ (sec.)}$
Deceleration time	$ta = \frac{(JM + JL) \times \Delta N}{9.56 \times (TB + TL)} \text{ (sec.)}$
Conditions	J.M.: Moment of inertia of motor (kg.m²) JL: Moment of inertia of load (kg.m²) (converted into value on motor shaft) ΔN: Difference in rotating speed between before and after acc. or dce. (min.¬¹) T.L: Load forque (N.m) T.M.: Motor rated torque x 1.1 (N.m) V/f control : Motor rated torque x 1.2 (N.m) Vector operation control TB: Motor rated torque x 0.2 (N.m) (When a braking resistor or a braking resistor unit is used: (Motor rated torque x 0.8-1.0 (N.m)

Allowable torque characteristics

When a standard motor is combined with an inverter to perform variable speed operation, the motor temperature rises slightly higher than it normally does during commercial power supply operation. This is because the inverter output voltage has a sinusoidal (approximate) PWM waveform. In addition, the cooling becomes less effective at low speed, so the torque must be reduced according to the


frequency. When constant-torque operation must be performed at low speeds, use a Toshiba VF motor designed specifically for use with inverters.

When a motor is driven by an inverter, its operation is restricted by the inverter's overload current

when a motor is driven by an inverter, its operation is restricted by the inverter's overload current rating, so the starting characteristic is different from those obtained from commercial power supply operation.

Although the starting torque is smaller with an inverter than with the commercial power supply, a high starting torque can be produced at low speeds by adjusting the V/f pattern torque boost amount or by employing vector control. When a larger starting torque is necessary, select an inverter with a larger capacity and examine the possibility of increasing the motor capacity.

Peripheral devices



■ Built-in options

_	Dant in options				
No	o. Name	Function/Purpose, etc.	Refer to		
	Expanded terminal block card	This option is convenient for adding on special functions. (Type : ETB003Z, ETB004Z)			
(1	CC-Link communications card	his option enables CC-Link communications with a host controller or other PLC. (Type : CCL001Z)			
Q.	DeviceNet communications card	This option enables DeviceNet communications with a host controller or other PLC. (Type :DEV002Z)			
	PROFIBUS communications card	This option enables PROFIBUS communications with a host controller or other PLC. (Type : PDP002Z)			
@	PG feedback card (complimentary output/line driver output)	Higher performance operation is possible by combining with a motor equipped with a sensor. (Type: VEC004Z, VEC005Z, VEC007Z)			

Vo.	Name			Function/Purpos	se, etc.		Refer to			
3	Input AC reactor	or suppress ex Install this opti- capacity is 10 generating sou wiring leads.	fect of this option changes according to the impedance of the reactor. Consult us							
		Reactor		Effect						
		Heactor	Improved Power Factor	Harmonics	External Surge Suppression					
		Input AC Reactor	0	0	0	Overy: very effective				
4)	DC reactor	DC Reactor	Overy	Overy	×	○: effective ×: ineffective	P26			
		recommend jo when facilities	int use of the inpu where the inverter is	t reactor, that is s to be applied rec	effective in suppres quire high reliability.	the power factor. We sing external surges,				
⑤	EMC Directive compliant noise reduction filter (for European market)		that mounting on t			s a system (foot mount rate-standing for large-	P27			
6	EMC plate					r cables or to connect I attachment or as an	P28			
T	Braking resistor Braking unit	the deceleratio This resistor is	This operation is used when sudden deceleration or stops are frequently performed, or when the deceleration time must be shortened on loads having a large inertia. This resistor is for taking up energy during power generation braking. For 200kW or more inverter, it requires the braking unit.							
8	Motor-end surge voltage suppression filter (400 V types only)	using ultra high length, cable insulation of the voltage are pe	On systems that run 400 V class general-purpose motors by voltage-type PWM system inverters using ultra high-speed switching devices (e.g. IGBT), surge voltage, that is dependent on cable length, cable laying methods, cable constants, and other factors, sometimes causes the insulation of the motor winding to deteriorate. For this reason, measures for suppressing surge voltage are performed by installing a DC reactor or surge suppression filter on the inverter output end where the insulation-reinforced motor is used.							
9	Control power supply backup unit	main circuit por Use this option	wer supply. when backing up	only by the contr	ol power supply wh	n the inverter from the en the main circuit is c. (Model : CPS002Z)	P34			
100	USB communications conversion unit	the connector of	able, parameters c	an be easily adjus	sted, and data easily	eations. By connecting saved and written. cional functions (Model :	P33			
1	Communications cable	Connector cab CAB0013, CAB		sion unit and LE	D remote keypad.	(Model : CAB0011,	P33			
1	LCD remote keypad (installable on body)	"hiragana" and	Kanji display facil	itates parameter		ts 11-character, 8-line ed cable for the LCD 004Z)	P31			
13	LCD cable	Connector cabl	e for LCD remote k	eypad (Model : CA	AB0071, CAB0073, 0	CAB0075, CAB00710)	P31			
14)	LED remote keypad (w/ parameter writer function)	UP/DOWN key		d enter key. Setu		olay, RUN/STOP key, nree inverters can be	P31			
15	Heat sink outside protrusion option	This allows hea	at generated inside	panels to be redu	ced.		P32-33			
16	Operation panel	Has a built-in frequ	ency type, frequency set	ter and RUN-STOP (fo	orward run, reverse run) s	witch. (Model : CBVR-7B1)	P34			

Harmonic current and influence to power supply

Harmonics are defined as sinusoidal waves that is multiple frequency of commercial power (base frequency: 50Hz or 60Hz). Commercial power including harmonics has a distorted waveform.

Some electrical and electronic devices produce distorted waves in their rectifying and smoothing circuits on the input side. Harmonics produced by a device influence other electrical equipment and facilities in some cases (for example, overheating of phase advancing capacitors and reactors).

Measures for suppressing higher harmonics

No	Measures	Description
1	Connecting a reactor	The leakage of a harmonic current from an inverter can be restricted by connecting an input AC reactor (ACL) on the input side of the inverter or a DC reactor (DCL) to the DC section of the inverter.
2	Connecting a higher harmonic suppressing unit (SC7)	A PWM converter that shapes the waveform of an input current into a substantially sinusoidal waveform. The leakage of a harmonic current from a power supply can be restricted by connecting a harmonic suppressing unit.
3	Connecting a higher harmonic suppressing phase advancing capacitor	A harmonic current can be absorbed by the use of a phase advancing capacitor unit composed of a phase advancing capacitor and a DC reactor.
4	Multi-pulse operation of transformation	For delta-delta connection and delta-Y connection transformers, the effect of 12 pulses can be obtained by distributing the load evenly, and thus currents containing fifth-order and seventh-order harmonics can be suppressed.
5	Other measures	Harmonic currents can also be suppressed by the use of passive (AC) and active filters.

Built-in options

Here are the internal devices optionally available. There are two types of optional devices: Add-on type and Plug-in type.

Table of optional devices


Optio	n name	Function, purpose	Model	Type of installation
Expansion terminal function	Expansion I/O card1	Used to extend input and output terminals.	ETB003Z	Add-on
Expansion terminal function	Expansion I/O card2	Osed to exteria iriput and output terminals.	ETB004Z	Add-on
	CC-Link communication card	Used to connect to a CC-Link network for control.	CCL001Z	Add-on
Communication function	DeviceNet communication card	Used to connect to a DeviceNet network for control.	DEV002Z	Add-on
	PROFIBUS-DP communication card	Used to connect to a PROFIBUS-DP network for control.	PDP002Z	Add-on
	Push-pull 12V	Used to issue motor pulse train rate commands or used for sensor	VEC004Z	Plug-in
PG feedback	Push-pull 15V	vector control.	VEC005Z	Plug-in
	RS422-5V	vector control.	VEC007Z	Plug-in

Function of Expansion I/O card

	•					
Model	ETB003Z	ETB004Z				
Multifunction programmable contact input	No-voltage conta Sink logic input (ON: Less than	grammable contact input : 4 points act input (24Vdc-5mA or less) (at a common voltage of 24V) Source logic input 10Vdc ON: 11Vdc or more OFF: Less than 5Vdc				
Multifunction programmable open collector output	Driving current: I Max. 20mA when	grammable open collector output : 2 points Vax. 50mA when an external power source is used n the internal power source is used 12V (min) to 30V (max)				
Multifunction programmable relay contact output	1C contact confi 250Vac-2A (co	guration os¢=1), 250Vac-1A (cos¢=0.4), 30Vdc-1A				
Differential current input	Disable	Current input: 20mA or less Voltage input: Differential voltages 5V or less, -10V or more, +10V or less				
Analog input	Disable	Current input: 20mA or less Voltage input: 0V to 10V				
Monitor output	Disable	Voltage output: -10V to 10V, 0V to 10V Current output: 0mA to 20mA				
Pulse train input	Disable	Input pulse specifications Voltage: Max. 5V				
External thermal trip input	Resistance between TH+ and TH- Error: Approx. 50Ω or less or approx. 3kΩ or more Recovery from error: Approx. 1.8kΩ					
24V power output	24Vdc - 60mA m	nax				
-10V power output	-10Vdc -10mA					
Contact input common terminal	Common termin	als for contact input				

How to install

Add-on type devices and insertion type devices are installed in different ways. Install them correctly, as shown in the figures below.




Function of PG feedback card

Model	VEC004Z, VEC005Z	VEC007Z			
Sensor vector control operation	Speed control operation: Zero-speed - Speed control range: Zero-speed - 1:1000 (1000p				
PG method	Complementary method, open collector method	Line drive method			
PG cable length	Max. 100m (complementary method)	Max. 30m			
PG supply power	VEC004Z: 12V-160mA VEC005Z: 15V-150mA	5V-160mA			
Maximum pulse input frequency	300kHz or less * If a two-phase open collector is used, a study needs to be made to determine derating factor. For details, refer to the operating manual for the optional devi Pulse duty: 50±10%				
Pulse input voltage	12Vdc~24Vdc	Line driver (LTC485 or equivalent)			


■ Dimension of depth that installed option

Depending on the capacity, the installation of an Add-on type device may increase

200V 0.4 to 45kW/400V 0.75 to 37kW




400V 45 to 75kW



200V 55, 75kW/400V 90 to 500kW

Note) The inverters of these capacities come equipped with an Add-on type option case as standard.
When installing an optional Add-on type device, remove the case.



External options

Voltage class	Applicable motor (kW)	Inverter model	Input AC reactor (ACL)	DC reactor (DCL) Note 4)	EMC Directive compliant noise reduction filter	Braking resistor Note 1), 2)	Motor end surge voltage suppression filter	
	0.4	VFAS1-2004PL	PFL-2005S	DCL-2007		PBR-2007		
	0.75	VFAS1-2007PL	PFL-20035	DCL-2007		PBN-2007		
	1.5	VFAS1-2015PL	PFL-2011S	DCL-2022		PBR-2022		
	2.2	VFAS1-2022PL	FFL-20113	DUL-EUEE	Built-in	FBN-2022		
	3.7/4.0	VFAS1-2037PL	PFL-2018S	DCL-2037		PBR-2037		
	5.5	VFAS1-2055PL	PFL-2025S	DCL-2055		PBR3-2055	İ	
	7.5	VFAS1-2075PL	PFL-2050S	DCL-2110		PBR3-2075		
0001	11	VFAS1-2110PM	11L-20000		EMF3-4072E	PBR3-2110		
200V class	15	VFAS1-2150PM				PBR3-2150	_	
5.455	18.5	VFAS1-2185PM	PFL-2100S		EMF3-4090F	FBN3-2130		
	22	VFAS1-2220PM		Built-in	LIVII O 40001	PBR3-2220		
	30	VFAS1-2300PM	PFL-2150S			I BIIO-EEEO		
	37	VFAS1-2370PM	11121303		EMF3-4180H			
	45	VFAS1-2450PM	PFL-2200S			PBR-222W002		
	55	VFAS1-2550P	PFL-2300S	A + +				
	75	VFAS1-2750P	PFL-2400S	Attached as standard	EMF3-4300I	DGP600W-B1 [DGP600W-C1]		
	0.75	VFAS1-4007PL		DCL-2007			MSF-4015Z	
	1.5	VFAS1-4015PL	PFL-4012S	Note 3)		PBR-2007	WISF-4013Z	
	2.2	VFAS1-4022PL	PFL-40125	DCL-2022			MSF-4037Z	
	3.7/4.0	VFAS1-4037PL		Note 3)		PBR-4037	WIST-40372	
	5.5	VFAS1-4055PL				PBR3-4055	MSF-4075Z	
	7.5	VFAS1-4075PL	PFL-4025S	DCL-4110		PBR3-4075	WIST-4075Z	
	11	VFAS1-4110PL				PBR3-4110	MSF-4150Z	
	15	VFAS1-4150PL		DCL-4220		PBR3-4150	WISF-4150Z	
	18.5	VFAS1-4185PL	PFL-4050S			FBN3-4130	MSF-4220Z	
	22	VFAS1-4220PL				PBR3-4220		
	30	VFAS1-4300PL				PBN3-4220	MSF-4370Z	
	37	VFAS1-4370PL	PFL-4100S	Built-in		PBR-417W008		
	45	VFAS1-4450PL					MSF-4550Z	
	55	VFAS1-4550PL	PFL-4150S				WISF-4550Z	
	75	VFAS1-4750PL	PFL-41505				MSF-4750Z	
400V	90	VFAS1-4900PC	PFL-4300S					
class	110	VFAS1-4110KPC	FFL-43003		Built-in	DGP600W-B2		
	132	VFAS1-4132KPC	PFL-4400S			[DGP600W-C2]		
	160	VFAS1-4160KPC	1112-44003					
	200	VFAS1-4200KPC				PB7-4200K Note 2)		
	220	VFAS1-4220KPC	PFL-4600S			DGP600W-B3 [DGP600W-C3]		
	280	VFAS1-4280KPC	PFL-4800S	Attached as standard		PB7-4200K Note 2) DGP600W-B4 [DGP600W-C4]	_	
	355	VFAS1-4355KPC	PFL-4450S ×2 (parallel)			PB7-4400K Note 2) DGP600W-B3 ×2 (parallel) IDGP600W-C3		
	400	VFAS1-4400KPC				×2 (parallel)]		
	500	VFAS1-4500KPC	PFL-4613S ×2 (parallel)			PB7-4400K Note 2) DGP600W-B4 ×2 (parallel) [DGP600W-C4 ×2 (parallel)]		

Note 1) Model in square brackets is fitted with top cover.


Note 2) To use a 400V/200kW inverter or larger in combination with an external braking resistor (DGP600 series), a braking unit (PB7) is also needed.


Note 3) These reactors are usable for each of 200V class and 400V class.


Note 4) Be sure to connect DC reactor to 200V-55kW or more and 400V-90kW or more inverter. (Not necessary for DC power input.)


Input AC reactor


External dimensions

















Connection diagram





In case of using control power supply backup unit (option)



For 400V class 355 to 500kW, be sure to connect the AC reactor in parallel


Madel	Doting	Investor tune				Dim	ensid	ons (n	nm)				External	Tarminolo	Approx.
Model	Rating	Inverter type	W	Н	D	H2	Α	E	F	G	T	K	dimension diagram	Terminals	weight (kg)
PFL-2005S	3φ-230V-5.5A-50/60Hz	VFAS1-2004PL、2007PL	105	115	72.5	_	90	55	5	_		_		Terminal block M3.5	1.2
PFL-2011S	3φ-230V-11A-50/60Hz	VFAS1-2015PL、2022PL	130	140	85	_	115	60	5	_		_	Α		2.3
PFL-2018S	3φ-230V-18A-50/60Hz	VFAS1-2037PL	130	140	85	_	115	60	5	_		_		Terminal block M4	2.5
PFL-2025S	3φ-230V-25A-50/60Hz	VFAS1-2055PL	125	130	100	-	50	83	7	_		_			2.6
PFL-2050S	3φ-230V-50A-50/60Hz	VFAS1-2075PL~VFAS1-2110PM	155	140	115	_	50	95	7	_		_	В	Terminal block M6	3.4
PFL-2100S	3φ-230V-100A-50/60Hz	VFAS1-2150PM、2185PM、2220PM	230	210	150	-	60	90	8	_		_		Terminal block M8	8.2
PFL-2150S	3φ-230V-150A-50/60Hz	VFAS1-2300PM、2370PM	175	220	160	290	60	110	8	_		_		Ring terminal 60-10	11.3
PFL-2200S	3φ-230V-200A-50/60Hz	VFAS1-2450PM	195	240	170	320	65	115	10	_		_	С	Ring terminal 80-10	15.1
PFL-2300S	3φ-230V-300A-50/60Hz	VFAS1-2550P	235	280	200	370	75	128	10	_		_		Ring terminal 150-10	23.1
PFL-2400S	3φ-230V-400A-50/60Hz	VFAS1-2750P	260	330	230	_	90	200	12	300	9	13	D	φ13	30
PFL-4012S	3φ-460V-12.5A-50/60Hz	VFAS1-4007PL~VFAS1-4037PL	125	130	95	_	50	79	7	_	-	_		Terminal block M4	2.3
PFL-4025S	3φ-460V-25A-50/60Hz	VFAS1-4055PL~VFAS1-4110PL	155	155	110	_	50	94	7	_	_	_	В	TOTTIMINAL BIOOK WIT	4.9
PFL-4050S	3φ-460V-50A-50/60Hz	VFAS1-4150PL、4185PL、4220PL	155	165	140	_	50	112	7	_	-	_	Ь	Terminal block M6	6.6
PFL-4100S	3φ-460V-100A-50/60Hz	VFAS1-4300PL、4370PL、4450PL	235	250	170	_	75	105	10	_	-	_		Terminal block M8	17.6
PFL-4150S	3φ-460V-150A-50/60Hz	VFAS1-4550PL、4750PL	235	280	190	360	75	115	10	_		_	С	Ring terminal 80-10	20.3
PFL-4300S	3φ-460V-300A-50/60Hz	VFAS1-4900KPC、4110KPC	260	380	230	_	90	200	12	280	9	13	D	φ13	38
PFL-4400S	3φ-460V-400A-50/60Hz	VFAS1-4132KPC、4160KPC	260	380	230	_	90	200	12	300	9	13	D	φ13	42
PFL-4600S	3φ-460V-600A-50/60Hz	VFAS1-4200KPC、4220KPC	440	465	290	_	280	250	15	445	12	18	Е	φ18	75
PFL-4800S	3φ-460V-800A-50/60Hz	VFAS1-4280KPC	440	540	290	-	280	250	15	445	12	18		φ18	90
PFL-4450S	3φ-480V-450A-50/60Hz	VFAS1-4355KPC Note 1),4400KPC Note 1)	385	230	320	_	340	225	11	250	_	13	F	φ13	68
PFL-4613S	3φ-480V-613A-50/60Hz	VFAS1-4500KPC Note 1)	400	245	385	_	400	300	13.5	26.5	_	13	Г	φ13	85


Note 1) Be sure to connect the AC reactor in parallel.


DC reactor


For 200V class 11 to 45kW and 400V class 18.5 to 75kW, DC reactor is built-in standard. Please use these external options when requiring the further improvement of the power factor and reducing harmonics.


External dimensions











Model	Rated	Inverter type			Dimer	nsions	(mm)			External dimension	Terminal	Approx. weight
Model	current	inverter type	W	Н	D	Х	Υ	d1	d2	diagram	remina	(kg)
DCL-2007 Note 2)	7A	VFAS1-2004PL、2007PL	92	65	70	82	_	_	_	Α	Ring terminal V2-3.5	1.2
DCL-2022	14A	VFAS1-2015PL、2022PL	86	110	80	71	64	_	_	В	M4	2.2
DCL-2037	22.5A	VFAS1-2037PL	86	110	85	71	70	_	_		IVI4	2.5
DCL-2055	38A	VFAS1-2055PL	75	130	140	50	85	85	55		M5	1.9
DCL-2110	75A	VFAS1-2075PL~VFAS1-2110PM	100	150	150	65	85	95	55	С	М6	2.4
DCL-2220	150A	VFAS1-2150PM、2185PM、2220PM	117	170	190	90	90	130	60		M8	4.3
DCL-2370	225A	VFAS1-2300PM、2370PM	150	215	200	130	95	135	65	D	M8	5.9
DCL-2450	300A	VFAS1-2450PM	150	225	230	130	125	150	80	ם ו	M10	7.8
DCL1-2550	316A	VFAS1-2550P Note 3)				Dofor	to out	araal d	manai	on of Invert		
DCL1-2750	382A	VFAS1-2750P Note 3)	Refer to external dimension of Inverter.					∄.				
DCL-2007 Note 2)	7A	VFAS1-4007PL、4015PL Note 1)	92	65	70	82	_	_	_	А	Ring terminal V2-3.5	1.2
DCL-2022	14A	VFAS1-4022PL、4037PL Note 1)	86	110	80	71	64	_	_	В	M4	2.2
DCL-4110	38A	VFAS1-4055PL、4075PL、4110PL	95	150	165	70	90	105	60		M5	3.0

Refer to external dimension of Inverter.

М6

M8

M8

3.7

9.8

11.5

105 160 185 80 100 120 65

150 180 225 120 125 145 80

170 215 230 150 125 150 80

702A Note 1) These reactors are usable for each of 200V class and 400V class.

150A

225A

243A

290A

351A

486A

575A

DCL-4220

DCL-4450

DCL-4750

DCL1-4900

DCL1-4110K

DCL1-4132K

DCL1-4160K

DCL1-4200K

DCL1-4280K

Note 2) Please modify the terminal according to size of inverter main terminal. Note 3) Be sure to connect DC reactor to 200V-55kW or more and 400V-90kW or more inverter.

VFAS1-4150PL、4185PL、4220PL

VFAS1-4300PL、4370PL、4450PL

VFAS1-4220KPC、4280KPC Note 3)

VFAS1-4550PL、4750PL

VFAS1-4900PC Note 3)

VFAS1-4110KPC Note 3)

VFAS1-4132KPC Note 3)

VFAS1-4160KPC Note 3)


VFAS1-4200KPC Note 3)

EMC Directive compliant noise reduction filter


For 200V class 0.4 to 7.5kW and 400V class 0.75 to 500kW, EMC noise filter is built-in standard. Please use these external options depended on the length of the cable between inverter and motor.

	Requir	ements	Conducted noise	Conducted noise		
Inverter type	ppe PWM carrier Leng co (kHz) c		IEC61800-3 category C2 (EN55011 classA Group1)	IEC61800-3 category C3 (EN55011 classA Group2)		
VFAS1-2004PL-2022PL	4	10	Built-in filter	_		
VFAS1-4007PL-4037PL	16	5	Built-iii liitei			
VFAS1-2037PL-2075PL	4	10				
VFAS1-4055PL-4150PL	16	5				
VFAS1-4185PL-4750PL	2.5	25	_	Built-in filter		
VI A3 1-4 183FE-4730FE	16	25				
VFAS1-4900PC-4500KPC	2.5	50				


(1) Foot mount type EMC noise filter



Connection diagram



EMC noise filter can be foot mounted and side mounted.






Model	Rated current	Inverter type					Dime	nsions	(mm)				Approx. leak (mA) N	age current	Approx. weight	
Model	(A)	inverter type	W	Н	D	W1	H1	W2	H2	Е	F	G	Power source A	Power source B	(kg)	
EMF3-4012A	12	VFAS1-2004PL~2015PL	130	290	39	105	275		275	4.5	11	10	5	35	2.5	
EIVIF3-4012A	12	VFAS1-4007PL~4022PL	130	290	39	105	2/5		2/5	4.5	11	10	9	70	2.5	
EMEO 4000D	26	VFAS1-2022PL~2037PL	155	324	49	130	309		309	4.5	11	10	6	42	3.5	
EMF3-4026B	20	VFAS1-4037PL	155	324	49	130	309		309	4.5	11	10	11	83	3.5	
EMF3-4035C 35		VFAS1-2055PL	175	370	59	150	355		355		11	11	4	25	5.0	
EIVIF3-4035C	35	VFAS1-4055PL, 4075PL	175	370	59	150	355		300	5.5	11	' '	6	44	5.0	
EMF3-4046D 4	46	VFAS1-2075PL	010	200	59	190	365		365	5.5	11	11	12	91	6.0	
EIVIF3-4046D	40	VFAS1-4110PL	210	360	380	ວອ	190	300		300	5.5	11	' '	24	183	0.0
EMF3-4072E	72	VFAS1-2110PM,2150PM	220	498.5	62	190	460		479.5	6.6	11	12	25	195	11	
EIVIF3-4072E	/2	VFAS1-4150PL, 4185PL	230	430.0	02	190	460	_	4/8.5	0.0	11	12	52	390	11	
EMF3-4090F	90	VFAS1-2185PM,2220PM	040	521.5	79	200	502.5	40	502.5	6.6	11	12	36	268	15	
EIVIF3-4090F	90	VFAS1-4220PL	240	521.5	/9	200	502.5	40	502.5	0.0	11	12	70	535	15	
EMF3-4092G	92	VFAS1-4300PL,4370PL	240	650	79	200	631	40	631	6.6	11	12	70	535	16	
EMF3-4180H	180	VFAS1-2300PM~2450PM	220	750	119	200	705	90	725	0	10	18	70	537	40	
	180	VFAS1-4450PL~4750PL	320	750	119	280	725	80 72	725 9	9 18		10	142	1075	7 40	

Note 1) These values are referential ones of single piece of EMC noise filter. For 200V class, 200V-60Hz power source. For 400V class, 400V-60Hz power source.

(2) EMC noise filter

External dimensions diagram




Model	Rated	Inverter type	Term	inal	Approx.	Approx. leakage current(mA) Note 2)		
Model	current (A)		Main circuit Grounding		weight (kg)	Power source A	Power source B	
EMF3-4300I	300	VFAS1-2550P, 2750P	Busbar 25 * 6	M12	13.2	3	180	
EIVIF3-4300I	300	VFAS1-4900PC~4132KPC	M10	IVIIZ	13.2	5	350	
EMF3-4600J	580	VFAS1-4160KPC~4280KPC, 4355KPC Note 1), 4400KPC Note 1) 4500KPC Note 1)	Busbar 32*8 M10	M12	15	5	350	

Note 1) Be sure to connect the EMC noise filter in parallel.

Note 2) These values are referential ones of single piece of EMC noise filter. For 200V class, 200V-60Hz power source. For 400V class, 400V-60Hz power source.

Connection diagram

EMC noise




For 400V class 355 to 500kW

Power source A	Power source B
with.	W =

EMC plate

EMC plate is attached in standard for 400V class of WP1 type up to 18.5kW.

External dimensions





Model	Inverter type	Dimension (mm) H2		
EMP101Z	VFAS1-2004~2015PL			
LIVIFTOTZ	VFAS1-4007~4022PL	55		
EMP102Z	VFAS1-2022~2037PL	33		
EIVIP 1022	VFAS1-4037PL			
EMP103Z	VFAS1-2055PL, 2075PL			
EIVIP 1032	VFAS1-4055~4110PL	65		
EMP104Z	VFAS1-2110,2150PM	65		
EIVIP 1042	VFAS1-4150, 4185PL			
EMP105Z	VFAS1-2185,2220PM			
EIVIP 1052	VFAS1-4220PL			
EMP106Z	VFAS1-4300,4370PL	120		
EMP107Z	VFAS1-2300~2450PM			
EMP108Z	VFAS1-4450~4750PL			

The wire clamps and screws are attached to the EMC plate for fixing the shielded cables on the EMC plate.


Motor end surge voltage suppression filter (Only 400V class)

External dimensions





Connection diagram



■ Countermeasure of motor end surge voltage


At the system of operation of the 400V class motor by the voltage type PWM inverter with using super high-speed switching device(ex.IGBT). the degradation of insulation of motor wiring may be occurred by the length conditions of the cable, laid down of the cable and the constants of the cable.


- In this case, the following countermeasures are suggested.
- 1) Use of the enhanced insulation type of motor
- 2) Suppress the surge voltage by AC reactors in the load side or surge suppression filter.


Madal	Applicable motor			Dime	ensions (mm)			External dimension	Terminal screw	Approx. weight
Model	(kW)	Α	В	С	D	E	F	G	diagram	Terriiridi Screw	(kg)
MSF-4015Z	0.4、0.75、1.5	310	255	300	200	270	55	189		M4	12
MSF-4037Z	2.2、3.7	310	255	300	200	270	55	209		M4	20
MSF-4075Z	5.5、7.5	310	315	350	200	320	55	249	Α	M5	30
MSF-4150Z	11, 15	330	350	400	200	370	65	289		M6	40
MSF-4220Z	18.5、22	330	400	400	200	370	65	279		M6	52
MSF-4370Z	30、37	426	375	512	260	490	83	350	В	M8	75
MSF-4550Z	45、55	450	395	632	260	610	95	365		M10	110
MSF-4750Z	75	450	415	700	260	678	95	385		M10	120


Braking resistor


External dimensions, connection diagram














Braking resistor (PBR)

Voltage	_	Model	Rating		Dim	nensio	ons (r	nm)		External	Connection	Approx.
class	Type		Note 2), 3)	Α	В	С	D	Е	G	diagram		weight (Kg)
		PBR-2007	120W-200Ω									
		PBR-2022	120W-75Ω	42	182	20	4.2	172	_	Α	Е	0.28
		PBR-2037	120W-40Ω									
		PBR3-2055	20Ω-240W (40Ω-120W×2P)		320	115			50			4
	Standard	PBR3-2075	15Ω-440W (30Ω-220W×2P)				110	230		_		4.5
		PBR3-2110	10Ω-660W (30Ω-220W×3P)	120	350	190	110	230	150	В		5
		PBR3-2150	7.5Ω-880W (30Ω-220W×4P)									5.5
200V		PBR3-2220	3.3Ω-1760W (27Ω-220W×8P)	248	430	200	190	414	47	С		13
		PBR-222W002	2Ω-2200W(20Ω-220W×10P)	297	445	200	220	429	47	U	F	13
	200W class	PBR-202W □□□	40Ω, 75Ω-240W	1.00	320	115	110	230	50	В	'	3
	500W class	PBR-208W □□□	15Ω, 20Ω, 40Ω, 75Ω-880W	120	350	190	110	230	150			6
	1.5kW class	PBR-217W □□□	15Ω, 20Ω, 40Ω, 75Ω-1760W	248	430	200	190	414	47)		13
	2.5kW class	PBR-226W □□□	2Ω, 3.3Ω, 7.5Ω, 10Ω, 15Ω, 20Ω, 40Ω-2640W	297	445	200	220	429	47	С		14
	3.5kW class	PBR-235W □□□	3.3Ω, 7.5Ω, 15Ω, 20Ω-3520W	397	445	200	320	429	47	_		19
	5kW class	PBR-252W □□□	2Ω, 3.3Ω, 7.5Ω, 15Ω-5280W	520	616	220	420	600	47	D		36
		PBR-2007	120W-120Ω	42	182	20	4.2	172	_	Α	Е	0.28
		PBR-4037	120W-160Ω		102	LO	4.2	172		_ A		0.20
		PBR3-4055	80Ω-240W (160Ω-120W×2P)		320	115			50			4
	Standard	PBR3-4075	60Ω-440W (120Ω-220W×2P)	120			110	230		В		4.5
	Stariuaru	PBR3-4110	40Ω-660W (120Ω-220W×3P)	120	350	190	110	200	150	Ь		5
		PBR3-4150	30Ω-880W (120Ω-220W×4P)									5.5
4001/		PBR3-4220	15Ω-1760W (30Ω-220W×4P2S)	248	430	200	190	414	47	С		13
400 V		PBR-417W008	8Ω-1760W (16Ω-220W×4P2S)		100		100		17		_	13
	200W class	PBR-402W □□□	160Ω-240W	120	320	115	110	230	50	В	F	3
	500W class	PBR-408W □□□	40Ω, 60Ω, 80Ω, 160Ω-880W	120	350	190	110	200	150			6
	1.5kW class	PBR-417W □□□	30Ω, 40Ω, 60Ω, 80Ω-1760W	248	430	200	190	414	47	С		13
	2.5kW class	PBR-426W □□□	8Ω, 15Ω, 30Ω, 40Ω-2640W	297	445	200	220	429	47			14
		PBR-435W □□□	15Ω, 30Ω, 40Ω-3520W	397	445	200	320	429	47	D		19
	5kW class	PBR-452W □□□	8Ω, 15Ω, 30Ω, 40Ω-5280W	520	616	220	420	600	47	ט		36

Note 1) \[\limits_{\text{in}} \] in the type-form are numeric character. Please refer the "Selection of braking resistor" in the next page.


Note 2) The rating shows the synthetic resistor value (Ohm) and the synthetic resistor power (Wait). The word in the parentheses shows the composition of resistor elements.


Note 3) The allowable continuous regenerative power differs on the resistor value or power tolerance. Please refer the "Selection of braking resistor" in the next page.

■ Braking resistor (DGP600)

Model		Dime	ensions ((mm) no	te 2)			Thermal relay(Th-Ry)	Approx.
With cover Note 1)	Rating	A/A1	D/D1	E/E1	F/F1	dimension diagram	diagram	Setting value(A)	weight (kg)
DGP600W-C1	1.7Ω-3.4kW	283/303	207/192	620/700	725/780			46	50
DGP600W-C2	3.7Ω-7.4kW	493/513	417/402	620/700	725/780			44	100
DGP600W-C3	1.9Ω-8.7kW				725/780			71	150
	2.5Ω-10.5kW	703/723	627/612	620/700		G	н	65	150
	5Ω-10kW							45	150
DGP600W-C4	1.4Ω-14kW	013/033	837/899	620/700	725/780			110	200
	1.7Ω-10kW	910/900	007/022	020/700	723/760			77	200
	With cover Note 1) DGP600W-C1 DGP600W-C2	With cover Note 1) Rating DGP600W-C1 1.7Ω-3.4kW DGP600W-C2 3.7Ω-7.4kW 1.9Ω-8.7kW 2.5Ω-10.5kW 5Ω-10kW 1.4Ω-14kW	With cover Note 1) Rating A/A1 DGP600W-C1 1.7Ω-3.4kW 283/303 DGP600W-C2 3.7Ω-7.4kW 493/513 1.9Ω-8.7kW 2.5Ω-10.5kW 703/723 5Ω-10kW 1.4Ω-14kW 913/933	With cover Note 1) Rating A/A1 D/D1 DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 1.9Ω-8.7kW 2.5Ω-10.5kW 703/723 627/612 5Ω-10kW 1.4Ω-14kW 913/933 837/822	With cover Note 1) Rating A/A1 D/D1 E/E1 DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 620/700 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 620/700 1.9Ω-8.7kW 2.5Ω-10.5kW 703/723 627/612 620/700 5Ω-10kW 1.4Ω-14kW 913/933 837/822 620/700	With cover Note 1) Rating A/A1 D/D1 E/E1 F/F1 DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 620/700 725/780 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 620/700 725/780 DGP600W-C3 2.5Ω-10.5kW 703/723 627/612 620/700 725/780 DGP600W-C4 1.4Ω-14kW 913/933 837/822 620/700 725/780	With cover Note 1) Rating Note 1) A/A1 D/D1 E/E1 F/F1 dimension diagram DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 620/700 725/780 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 620/700 725/780 DGP600W-C3 2.5Ω-10.5kW 703/723 627/612 620/700 725/780 DGP600W-C4 1.4Ω-14kW 913/933 837/822 620/700 725/780	With cover Note 1) Rating Note 1) A/A1 D/D1 E/E1 F/F1 dimension diagram Connection diagram DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 620/700 725/780 725/780 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 620/700 725/780 DGP600W-C3 2.5Ω-10.5kW 703/723 627/612 620/700 725/780 G DGP600W-C4 1.4Ω-14kW 913/933 837/822 620/700 725/780	With cover Note 1) Rating Note 1) A/A1 D/D1 E/E1 F/F1 dimension diagram Connection diagram Setting value(A) DGP600W-C1 1.7Ω-3.4kW 283/303 207/192 620/700 725/780 46 DGP600W-C2 3.7Ω-7.4kW 493/513 417/402 620/700 725/780 44 DGP600W-C3 2.5Ω-10.5kW 703/723 627/612 620/700 725/780 G H 65 5Ω-10kW 1.4Ω-14kW 913/933 837/822 620/700 725/780 H 110

Note 1) The braking resistors are designed for indoor type. Please use them with drip cover in case of water drop. But please note it is not for water proof protection type. Note 2) A,D,E,F are the dimensions of standard type. A1,D1,E1,F1 are the dimensions of those with drip cover type.





Note 1) In case of 400V class, please apply the 200V to the operation circuit by using control transformer or 200V power supply.

Note 2) Please twist the wire by 10 cm pitch. The distance between resistor power wiring and the control wiring should be over 20 cm.

Note 3) In case of TOSHIBA thermal relay, please make a short circuit with 8 mm2 wire between the 2/T1 and 6/T3 of the thermal relay.

Selection of braking resistor

This is used for the quick deceleration, the frequent deceleration stop or shortening the deceleration time at the large inertia load. This resistor consumes the regenerative energy when regenerative braking operation. In case of over 3% ED, please select the allowable continuous regenerative power (Watt) in the following table.

1) The continuous regenerative load likes an elevator

2) Deceleration stops at large inertia machine

- 3) Frequent deceleration stop by using braking resistors

	Appliachle						Model				
/oltage	Applicable motor	Inverter type		Standard type				High frequenc	y type Note 2)		
	(kW)	Note 1)	PBR	DGP600	Note 4)			PBR			DGP600
			Note 3)	Standard	With cover Note 5)	500W class	1.5kW class	2.5kW class	3.5kW class	5kW class	10kW class(Note
	0.4	VFAS1-2004PL	PBR-2007	_	_	PBR-208W075	_	_	-	_	_
	0.75	VFAS1-2007PL	(200Ω-90W)	_	_	(75Ω-540W)	PBR-217W075 (75Ω-1200W)	_	_	_	_
	1.5	VFAS1-2015PL	PBR-2022	-	-				_	-	-
	2.2	VFAS1-2022PL	(75Ω-90W)	-	-	PBR-208W040 (40Ω-570W)	PBR-217W040 (40Ω-1160W)	PBR-226W040 (40Ω-1630W)	_	-	-
	3.7/4.0	VFAS1-2037PL	PBR-2037 (40Ω-90W)	-	-	,	,	, , , , , ,	-	-	-
	5.5	VFAS1-2055PL	PBR3-2055 (20Ω-96W)	-	-	PBR-208W020 (20Ω-270W)	PBR-217W020 (20Ω-950W)	PBR-226W020 (20Ω-1580W)	PBR-235W020 (20Ω-2330W)	_	_
	7.5	VFAS1-2075PL	PBR3-2075 (15Ω-130W)	-	-	=	PBR-217W015 (15Ω-840W)	PBR-226W015 (15Ω-1350W)	PBR-235W015 (15Ω-2080W)	PBR-252W015 (15Ω-3330W)	_
0001	11	VFAS1-2110PM	PBR3-2110 (10Ω-200W)	_	_	_	PBR-217W010 (10Ω-470W)	PBR-226W010 (10Ω-1250W)	PBR-235W010 (10Ω-1960W)	PBR-252W010 (10Ω-3200W)	_
200V	15	VFAS1-2150PM	PBR3-2150	_	_	-	_	PBR-226W7R5	PBR-235W7R5	PBR-252W7R5	_
	18.5	VFAS1-2185PM	(7.5Ω-270W)	-	_	İ	_	(7.5Ω-870W)	(7.5Ω-1380W)	(7.5Ω-3210W)	_
	22	VFAS1-2220PM	PBR3-2220	-	_	1	-	-	-	PBR-252W3R3	_
	30	VFAS1-2300PM	(3.3Ω-610W)	_	_	-	-	_	_	(3.3Ω-1760W)	_
	37	VFAS1-2370PM		-	_		-	-	-	PBR-226W7R5	
	45	VFAS1-2450PM	PBR-222W002 (2Ω-1000W)	_	_	_	_	_	-	×3 (parallel)	DGP600W-B4/0
	55	VFAS1-2550P	(212-1000W)	_	_	_	_	_	_	(2.5Ω-2610W)	(1.7Ω-10kW)
	75	VFAS1-2750P	_	DGP600W-B1 (1.7Ω-3.4kW)	DGP600W-C1	1	_	_	-	_	
	0.75	VFAS1-4007PL		(1.712=3.4KW)	(1.712-3.4KW)	DDD 400W100	_	_	_	_	_
	1.5	VFAS1-4015PL	PBR-2007	_	_	PBR-408W160 (160Ω-570W)	_	_	_	_	_
	2.2	VFAS1-4022PL	(200Ω-90W)	_	_		PBR-417W080 (80Ω-1090W)	_	_	_	_
	3.7/4.0	VFAS1-4037PL	PBR-4037 (160Ω-90W)	_	_	PBR-408W080	(80Ω-1090W)				
	5.5	VFAS1-4055PL	PBR3-4055 (80Ω-96W)	_	_	(80Ω-270W)	PBR-417W060				_
	7.5	VFAS1-4075PL	PBB3-4075	_			(60Ω-1000W)	PBR-426W040 (40Ω-1250W)	PBR-435W040 (40Ω-1900W)	PBR-452W040 (40Ω-2250W)	
	11	VFAS1-4110PL	(60Ω-130W) PBR3-4110	_	_	_	PBR-417W040 (40Ω-490W)	(((
	15	VFAS1-4150PL	(40Ω-190W)	_	_	_	(40Ω-490W) —			DDD 4504000	_
	18.5	VFAS1-4185PL	PBR3-4150 (30Ω-270W)	_	_	_	_	PBR-426W030 (30Ω-870W)	PBR-435W030 (30Ω-1680W)	PBR-452W030 (30Ω-2700W)	_
	22	VFAS1-4220PL		_	_	_	_	-	-		_
	30	VFAS1-4300PL	PBR3-4220 (15Ω-540W)	_	_		_	_	_	PBR-452W015 (15Ω-1740W)	_
	37	VFAS1-4370PL	(1011 0 1011)	_	_		_	_	_	(1011 17 1011)	_
	45	VFAS1-4450PL			_				_	PBR-426W030	
400)/			PBR-417W008 (8Ω-1000W)		_					×3 (parallel)	
400V	55	VFAS1-4550PL VFAS1-4750PL	,		_		_		_	(10Ω-2610W)	DGP600W-B3/0 (5Ω-10kW)
	75			_	_				_		(OLZ-TOKW)
	90	VFAS1-4900PC					_	_	_	_	
	110	VFAS1-4110KPC		DGP600W-B2 (3.7Ω-7.4kW)	DGP600W-C2 (3.7Ω-7.4kW)		_	_	_	_	DGP600W-B3/0
	132	VFAS1-4132KPC		(=:/22 /:(**)	(3.712 7100)		_	_		_	,
	160	VFAS1-4160KPC	_	PB7-4200K	PB7-4200K	_	_	_	_	_	
	200	VFAS1-4200KPC	_	DGP600W-B3	DGP600W-C3	-	_	_	_	_	_
	220	VFAS1-4220KPC		(1.9Ω-8.7kW)	(1.9Ω-8.7kW)						
	280	VFAS1-4280KPC	-	PB7-4200K DGP600W-B4 (1.4Ω-14kW)	PB7-4200K DGP600W-C4 (1.4Ω-14kW)	_	_	_	_	_	_
	355	VFAS1-4355KPC	-	PB7-4400K	PB7-4400K	-	-	-	-	-	-
	400	VFAS1-4400KPC	-	DGP600W-B3 ×2 (parallel)	DGP600W-C3 ×2 (parallel)	Ī	-	-	-	-	-
	500	VFAS1-4500KPC	-	PB7-4400K DGP600W-B4 ×2 (parallel)	PB7-4400K DGP600W-C4 ×2 (parallel)	-	-	-	-	-	-

Note 1) For 200kW or more inverter, it requires the braking unit.

Note 2) The figures in the parentheses show the synthetic resistor value (Ohm) and
the allowable continuous regenerative power (Wait).

Note 3) The guideline of the maximum braking at the standard type.

Note 4) The necessary power in case of deceleration from 60Hz at one time per 120 seconds periods at 30 seconds deceleration time for the 10 times of the motor inertia. please contact our agency when large inertia or quick deceleration.

Note 5) The braking resistors are designed for indoor type. Please use them with drip cover in case of water drop. But please note it is not for water proof protection type.


Applicable motor (kW)	Maximum braking power	Braking time
0.4~1.5	150%	6
2.2	100%	6
3.7~55	100%	3
75	100%	2

Braking unit


Model	PB7-4200K	PB7-4400I
Threshold voltage	785V	±1%
Maximum DC voltage	850V	
Maximum braking power at 785VDC	420kW	750kW

External dimensions PB7-4200K is mechanically mounted on the left-hand side of the inverter.

Approx. weight 30kg




PB7-4400K Approx. weight 80kg




LCD Remote Keypad


External dimensions




Installation on the unit



Installation on the panel





Palm top operation




LED Remote Keypad


External dimensions





Panel cutout dimensions








·LED Remote Keypad:RKP002Z ·Communication cable (option) Model:CAB0011(1m) CAB0013(3m) CAB0015(5m)


Heatsink outer option


This options enable the heatsink parts of the backside of inverter that generate much heat to be located at the outside of the panel. This is effective for the small sizing of the totally-enclosed box by reducing the heat values inside the box.














USB communications conversion unit






Control power supply backup unit




Operation panel (Model: CBVR-7B1)


External dimensions




Connection diagram



Frequency meter (QS-60T (80Hz-1mAdc))



FRH-KIT



To users of our inverters: Our inverters are designed to control the speeds of three-phase induction motors for general industry.

A Precautions

- * Read the instruction manual before installing or operating the inverter unit and store it in a safe place for reference.
- * When using our inverters for equipment such as nuclear power control, aviation and space flight control, traffic, and safety, and there is a risk that any failure or malfunction of the inverter could directly endanger human life or cause injury, please contact our headquarters, branch, or office printed on the front and back covers of this catalogue. Special precautions must be taken and such applications must be studied carefully.
- * When using our inverters for critical equipment, even though the inverters are manufactured under strict quality control always fit your equipment with safety devices to prevent serious accident or loss should the inverter fail (such as issuing an inverter failure signal).
- * Do not use our inverters for any load other than three-phase induction motors.
- * None of Toshiba, its subsidiaries, affiliates or agents, shall be liable for any physical damages, including, without limitation, malfunction, anomaly, breakdown or any other problem that may occur to any apparatus in which the Toshiba inverter is incorporated or to any equipment that is used in combination with the Toshiba inverter. Nor shall Toshiba, its subsidiaries, affiliates or agents be liable for any compensatory damages resulting from such utilization, including compensation for special, indirect, incidental, consequential, punitive or exemplary damages, or for loss of profit, income or data, even if the user has been advised or apprised of the likelihood of the occurrence of such loss or damages.

For further information, please contact your nearest Toshiba Representative or International Operations-Producer Goods.

The information in this brochure is subject to change without notice.

TOSHIBA

TOSHIBA CORPORATION Industrial Systems Company

Electrical Apparatus & Measurement Department International Operations Division
1-1, Shibaura 1-chome, Minato-ku,
Takwa 105, 2001, Japan

Tokyo 105-8001,Japan

Tel.: (03)3457-4911 Fax.: (03)5444-9268

06-12 (AB)8696A **(AB**)

